




STATIONARY EXTRUDED ALUMINUM ARCHITECTURAL BLADE LOUVER

Visible Mullion Louver Type	K6096
Material	Extruded Aluminum (Alloy 6063-T5)
Stationary Blade	0.081 in. (2.06 mm)
Frame	0.081 in. (2.06 mm)
Louver Depth	6 in. (152.4mm)
Blade Angle	39°
Free Area – 4 ft. x 4 ft. Unit	8.35 sq. ft. (0.78 sq m)
Percent Free Area	52.1%
Free Area Velocity at Beginning Point of Water Penetration – 0.01 oz H₂O/sq. ft. Free Area	817 fpm (4.15 m/s)
Air Volume Flow Rate at Beginning Point of Water Penetration – 4 ft. x 4 ft. Unit	6,396 cfm (3.02 m ³ /s)
Pressure Drop at Beginning Point of Water Penetration	0.10 in. H ₂ O (0.025 kPa)



RECOMMENDED SPECIFICATION

GENERAL

Furnish and install where indicated on plans or described in schedules stationary, architectural blade Louver Type K6096 as designed and manufactured by The Airlite Company LLC, Schofield, Wisconsin. Louvers shall be furnished with bird screen, insect screen, supports, installation hardware and finishes as specified and as required for a complete installation.

PRODUCTS

Louvers shall be stationary, architectural blade Louver Type K6096 with visible vertical mullions (or Louver Type CB6096 with concealed vertical mullions). Louvers shall be 6-inches (152.4 mm) deep and assembled entirely from extruded aluminum components. Blades and frames shall be 0.081-inch (2 mm) thick extruded aluminum, alloy 6063-T5. Blades shall be stationary, horizontal and spaced 6-inches (152.4 mm) on center.

OPTIONAL WELDED ASSEMBLY

Join stationary blade, head, sill and jamb frames with fillet welds concealed from view, unless the size of the louver makes screwed connections between louver sections necessary. Louver blades shall be joined to each jamb frame with fillet welds produced with the Pulsed Gas Metal Arc Welding (GMAW/Mig) process.

STRUCTURAL DESIGN CRITERIA

Maximum single section size for model K6096 is 72 in. W x 144 in. H or 144 in. W x 72 in. H. Larger openings require field assembly of multiple louver sections to make up the overall opening size. Individual louver sections are designed to withstand a 25 PSF wind load (please consult Airlite if the louvers must withstand higher wind-loads). Structural reinforcing members may be required to adequately support and install multiple louver sections within a large opening. Structural reinforcing members along with any associated installation hardware is not provided by Airlite unless indicated otherwise by Airlite. Options and accessories including, but not limited to, screens, filter racks, louver doors, and blank off panels are not subject to structural analysis unless indicated otherwise by Airlite. Additional information on louver installation may be found in AMCA Publication #501, Louver Application Manual.

PERFORMANCE RATINGS

FREE AREA:	8.35 Square Feet (0.78 m ²)
MINIMUM FREE AREA VELOCITY at Beginning Point of Water Penetration:	817 fpm (4.15 m/s)
MINIMUM AIR VOLUME FLOW RATE at Beginning Point of Water Penetration:	6,396 cfm (3.02 m ³ /s)
MAXIMUM STATIC PRESSURE at Beginning Point of Water Penetration:	0.10 in. H ₂ O (0.025 kPa)


See page 4 for complete finish options

LOUVER TYPE K6096 PRODUCT DESCRIPTION & DETAILS

AIROLITE LOUVER TYPE K6096 is a versatile, horizontal blade, 6-inch (101.6 mm) deep architectural louver designed for applications that require intake and exhaust ventilation with moderate protection against water penetration. Louver Type K6096 is available with both visible vertical mullions and concealed mullions to complement and enhance exterior façade elements. Louver Type K6096 is an efficient louver with AMCA Licensed air performance and water penetration ratings that enable designers to select and specify this product with confidence. Please contact your local Airolite representative or the factory for assistance with the layout and design of supports systems when required.

VERTICAL SECTION DETAIL


PLAN SECTION DETAIL



LOUVER TYPE K6096 PERFORMANCE RATINGS


FREE AREA CHART - in square feet

Louver Height Inches	Louver Width in Inches											
	12	24	36	48	60	72	84	96	108	120	132	144
12	0.16	0.36	0.57	0.78	0.98	1.16	1.37	1.58	1.78	1.99	2.17	2.38
24	0.66	1.54	2.42	3.30	4.18	4.95	5.83	6.71	7.59	8.47	9.24	10.12
36	1.17	2.72	4.27	5.83	7.38	8.74	10.29	11.84	13.40	14.95	16.31	17.86
48	1.67	3.90	6.12	8.35	10.58	12.53	14.75	16.98	19.21	21.43	23.38	25.61
60	2.17	5.07	7.97	10.87	13.77	16.31	19.21	22.11	25.01	27.91	30.45	33.35
72	2.68	6.25	9.83	13.40	16.97	20.10	23.67	27.25	30.82	34.39	37.52	41.09
84	3.18	7.43	11.68	15.92	20.17	23.89						
96	3.69	8.61	13.53	18.45	23.37	27.67						
108	4.19	9.79	15.38	20.97	26.57	31.46						
120	4.70	10.97	17.23	23.50	29.77	35.25						
132	5.20	12.14	19.08	26.02	32.96	39.04						
144	5.71	13.32	20.94	28.55	36.16	42.82						



AIRFLOW RESISTANCE


(Standard Air - .075 lb./ft.³)



Louver Type K6096 resistance to airflow (pressure drop) varies depending on louver application (air intake or air exhaust). Free area velocities (shown) are higher than average velocity through the overall louver size. (Tested to Figure 5.5-6.5)

WATER PENETRATION


(Standard Air - .075 lb./ft.³)



The AMCA Water Penetration Test provides a method for comparing various louver models and designs as to their efficiency in resisting the penetration of rainfall under specific laboratory test conditions. The point of zero water penetration is defined as that velocity where the water penetration curve projects through .01 oz. of water (penetration) per sq. ft. of louver free area. ***The beginning point of water penetration for Louver Type K6096 is 817 fpm free area velocity.** These performance ratings do not guarantee a louver to be weatherproof or stormproof and should be used in combination with other factors including good engineering judgement in selecting louvers.

LOUVER TYPE K6096

METHOD OF INSTALLATION & ACCESSORY OPTIONS



FINISHES

Finish Type	Description/Application	Color Selection	Standard Warranty (Aluminum)
AAMA 2605 100% Fluoropolymer (FEVE) 2-Coat 70% Kynar® (PVDF) 3-Coat 70% Kynar® (PVDF) 4-Coat 70% Kynar® (PVDF)	"Best." The premier finish for extruded aluminum. Tough, long-lasting coating has superior color retention and abrasive properties. Resists chalking, fading, chemical abrasion and weathering.	Standard Colors: Any of the 27 standard colors shown can be furnished in 70% or 50% Kynar®, 100% Fluoropolymer or Baked Enamel. Mica Colors: Airlite offers 6 standard Mica colors for 70% Kynar® or 100% Fluoropolymer. Custom Colors: Custom color matching is available. Consult your Airlite representative for cost and/or lead-time implications if a custom color is required.	10 Years (20 Years Optional)
AAMA 2603 Baked Enamel	"Good." Provides good adhesion and resistance to weathering, corrosion and chemical stain.		1 Year
AA-M10C22A42 Integral Color Anodize	"Two-step" anodizing is produced by following the normal anodizing step with a second, colorfast process.	Light, Medium, Dark or Extra Dark Bronze; Champagne; Black	5 years
AA-M10C22A41 Clear Anodize 215 R-1	Clear, colorless and hard oxide aluminum coating that resists weathering and chemical attack.	Clear	5 years
AA-M10C22A31 Clear Anodize 204	Clear, colorless and hard oxide aluminum coating that resists weathering and chemical attack.	Clear	1 Year
Prime Coat	Louvers or architectural products shall be cleaned, pre-treated and receive a prime coat finish suitable for field painting. Airlite does not recommend prime coat or field painting of materials.		n/a
Mill	Materials may be supplied in natural aluminum or galvanized steel finish when normal weathering is acceptable and there is no concern for color or color change.		n/a

Finishes meet or exceed AAMA 2605, AAMA 2604, and AAMA 2603 requirements. Please consult www.airlite.com for complete information on standard and extended paint warranties. Paint finish warranties are not applicable to steel products.



P.O. Box 410, 525 Western Road, Schofield, WI 54476-0410 USA
 715.841.8757 • fax 715.841.8773 • www.airlite.com

Submittal K6096 August 2021
 Copyright ©2021 The Airlite Company, LLC

The Airlite Company, LLC reserves the right to make product changes.