


K8506

Combination Louver/Damper | Drainable Blade | Extruded Aluminum

Standard Construction

| | |
|------------------------------------|--|
| Frame | Heavy gauge extruded 6063-T5 aluminum, 6 in. (152 mm) x 0.081 in. (2 mm) nominal wall thickness |
| Blades | Drainable design, heavy gauge extruded 6063-T5 aluminum, 0.081 in. (2 mm) nominal wall thickness, positioned 37° and 45° on approximately 6 in. (152 mm) centers |
| Seals | Dual-durometer extruded vinyl blade seals, compressible stainless steel jamb seals |
| Temperature Restrictions | (-20° F) - (+180° F) (-29° C) - (+82° C) |
| Linkage | Exposed on-blade linkage |
| Louver Depth | 6 in. (152 mm) |
| Construction | Mechanically fastened |
| Finish | Mill |
| Minimum Size | 12 in. W x 16 in. H (305 mm W x 406 mm H) |
| Maximum Single Section Size | 120 in. W x 120 in. H (3048 mm W x 3048 mm H) Limited to 70 sq. ft. (6.5 sq. m) |
| Wind Load | 25 PSF (1.2 kPa) |



Performance Ratings



Airolite certifies that the K8506 louvers shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to Water Penetration and Air Performance ratings.

Louvers were tested in accordance with AMCA Standard 500-L.

Performance of 48 in. x 48 in. (1219 mm x 1219 mm) Louver

| | |
|--|------------------------------------|
| Free Area | |
| Area | 7.32 sq. ft. (0.680 sq. m) |
| Percent | 45.8% |
| Performance at Beginning Point of Water Penetration | |
| Free Area Velocity | 1035 fpm (5.258 m/s) |
| Max Intake Volume | 7576 cfm (3.576 m ³ /s) |
| Performance at 6,000 CFM (2.832 m³/s) Intake | |
| Pressure Drop | 0.094 in. wg (0.023kPa) |

Options and Accessories

- Actuators
- [Bird Screen](#)
- [Extended Sill](#)
- [Filter Rack/Filter](#)
- [Flange Frame](#)
- [Glazing Frame](#)
- [Insect Screen](#)
- [Mounting Angles](#)
- [Security Bars](#)
- [Variety of Architectural Finishes](#)
- 0.125 in. (3mm) nominal wall thickness

Product Details

[K8506 Leakage Chart](#)

[K8506 Standard Details](#)

Structural reinforcing members may be required to adequately support and install multiple louver sections within a large opening. Structural reinforcing members along with any associated installation hardware is not provided by Airolite unless indicated otherwise by Airolite. Options and accessories including, but not limited to, screens, filter racks, louver doors, and blank off panels are not subject to structural analysis unless indicated otherwise by Airolite.

AIROLITE[®]
The look that works.[™]

K8506

Combination Louver/Damper | Drainable Blade | Extruded Aluminum

Free Area Chart

Free Area Chart shows free area in square feet and square meters.

| Louver Height Inches (Meters) | Louver Width in Inches (Meters) | | | | | | | | | | | | | | | | | | |
|-------------------------------|---------------------------------|-------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | 12 | 18 | 24 | 30 | 36 | 42 | 48 | 54 | 60 | 66 | 72 | 78 | 84 | 90 | 96 | 102 | 108 | 114 | 120 |
| 0.30 | 0.46 | 0.61 | 0.76 | 0.91 | 1.07 | 1.22 | 1.37 | 1.52 | 1.68 | 1.83 | 1.98 | 2.13 | 2.29 | 2.44 | 2.59 | 2.74 | 2.90 | 3.05 | |
| 16 | 0.31 | 0.52 | 0.73 | 0.94 | 1.15 | 1.36 | 1.57 | 1.78 | 1.99 | 2.20 | 2.41 | 2.62 | 2.83 | 3.04 | 3.25 | 3.46 | 3.67 | 3.88 | 4.09 |
| 0.41 | 0.03 | 0.05 | 0.07 | 0.09 | 0.11 | 0.13 | 0.15 | 0.17 | 0.18 | 0.20 | 0.22 | 0.24 | 0.26 | 0.28 | 0.30 | 0.32 | 0.34 | 0.36 | 0.38 |
| 18 | 0.43 | 0.73 | 1.02 | 1.31 | 1.61 | 1.90 | 2.19 | 2.49 | 2.78 | 3.07 | 3.37 | 3.66 | 3.95 | 4.25 | 4.54 | 4.83 | 5.13 | 5.42 | 5.71 |
| 0.46 | 0.04 | 0.07 | 0.09 | 0.12 | 0.15 | 0.18 | 0.20 | 0.23 | 0.26 | 0.29 | 0.31 | 0.34 | 0.37 | 0.39 | 0.42 | 0.45 | 0.48 | 0.50 | 0.53 |
| 30 | 0.84 | 1.41 | 1.97 | 2.54 | 3.11 | 3.68 | 4.24 | 4.81 | 5.38 | 5.95 | 6.51 | 7.08 | 7.65 | 8.22 | 8.78 | 9.35 | 9.92 | 10.49 | 11.05 |
| 0.76 | 0.08 | 0.13 | 0.18 | 0.24 | 0.29 | 0.34 | 0.39 | 0.45 | 0.50 | 0.55 | 0.60 | 0.66 | 0.71 | 0.76 | 0.82 | 0.87 | 0.92 | 0.97 | 1.03 |
| 36 | 1.04 | 1.75 | 2.45 | 3.16 | 3.86 | 4.57 | 5.27 | 5.97 | 6.68 | 7.38 | 8.09 | 8.79 | 9.50 | 10.20 | 10.91 | 11.61 | 12.32 | 13.02 | 13.72 |
| 0.91 | 0.10 | 0.16 | 0.23 | 0.29 | 0.36 | 0.42 | 0.49 | 0.55 | 0.62 | 0.69 | 0.75 | 0.82 | 0.79 | 0.95 | 1.01 | 1.08 | 1.14 | 1.49 | 1.27 |
| 48 | 1.45 | 2.43 | 3.41 | 4.38 | 5.36 | 6.34 | 7.32 | 8.30 | 9.28 | 10.26 | 11.24 | 12.21 | 13.19 | 14.17 | 15.15 | 16.13 | 17.11 | 18.09 | 19.07 |
| 1.22 | 0.13 | 0.23 | 0.32 | 0.41 | 0.50 | 0.59 | 0.68 | 0.77 | 0.86 | 0.95 | 1.04 | 1.13 | 1.23 | 1.32 | 1.41 | 1.50 | 1.59 | 1.68 | 1.77 |
| 54 | 1.65 | 2.77 | 3.88 | 5.00 | 6.11 | 7.23 | 8.35 | 9.46 | 10.58 | 11.69 | 12.81 | 13.92 | 15.04 | 16.16 | 17.27 | 18.39 | 19.50 | 20.62 | 21.74 |
| 1.37 | 0.15 | 0.26 | 0.36 | 0.46 | 0.57 | 0.67 | 0.78 | 0.88 | 0.98 | 1.09 | 1.19 | 1.29 | 1.40 | 1.50 | 1.60 | 1.71 | 1.81 | 1.92 | 2.02 |
| 66 | 2.12 | 3.55 | 4.98 | 6.41 | 7.84 | 9.27 | 10.70 | 12.13 | 13.56 | 14.99 | 16.42 | 17.85 | 19.28 | 20.71 | 22.14 | 23.57 | 25.00 | 26.43 | 27.86 |
| 1.68 | 0.20 | 0.33 | 0.46 | 0.60 | 0.73 | 0.86 | 0.99 | 1.13 | 1.26 | 1.39 | 1.43 | 1.66 | 1.79 | 1.92 | 2.06 | 2.19 | 2.32 | 2.46 | 2.59 |
| 72 | 2.35 | 3.94 | 5.53 | 7.11 | 8.70 | 10.29 | 11.88 | 13.47 | 15.06 | 16.64 | 18.23 | 19.82 | 21.41 | 23.00 | 24.59 | 26.17 | 27.76 | 29.35 | 30.94 |
| 1.83 | 0.22 | 0.37 | 0.51 | 0.66 | 0.81 | 0.96 | 1.10 | 1.25 | 1.40 | 1.55 | 1.69 | 1.84 | 1.99 | 2.14 | 2.28 | 2.43 | 2.58 | 2.73 | 2.87 |
| 84 | 2.82 | 4.72 | 6.63 | 8.53 | 10.43 | 12.34 | 14.24 | 16.15 | 18.05 | 19.95 | 21.86 | 23.76 | 25.67 | 27.57 | 29.47 | 31.38 | 33.28 | 35.19 | 37.09 |
| 2.13 | 0.26 | 0.44 | 0.62 | 0.79 | 0.97 | 1.15 | 1.32 | 1.50 | 1.68 | 1.85 | 2.03 | 2.21 | 2.38 | 2.56 | 2.74 | 2.92 | 3.09 | 3.27 | 3.45 |
| 90 | 3.03 | 5.09 | 7.14 | 9.19 | 11.24 | 13.29 | 15.34 | 17.39 | 19.44 | 21.50 | 23.55 | 25.60 | 27.65 | | | | | | |
| 2.29 | 0.28 | 0.47 | 0.66 | 0.85 | 1.04 | 1.23 | 1.43 | 1.62 | 1.81 | 2.00 | 2.19 | 2.38 | 2.57 | | | | | | |
| 102 | 3.44 | 5.77 | 8.09 | 10.42 | 12.74 | 15.07 | 17.39 | 19.72 | 22.04 | 24.37 | 26.69 | 29.02 | 31.34 | | | | | | |
| 2.59 | 0.32 | 0.54 | 0.75 | 0.97 | 1.18 | 1.40 | 1.62 | 1.83 | 2.05 | 2.26 | 2.48 | 2.70 | 2.91 | | | | | | |
| 108 | 3.64 | 6.11 | 8.57 | 11.03 | 13.49 | 15.95 | 18.42 | 20.88 | 23.34 | 25.80 | 28.27 | 30.73 | 33.19 | | | | | | |
| 2.74 | 0.34 | 0.57 | 0.80 | 1.02 | 1.25 | 1.48 | 1.71 | 1.94 | 2.17 | 2.40 | 2.63 | 2.85 | 3.08 | | | | | | |
| 120 | 4.05 | 6.79 | 9.52 | 12.26 | 14.99 | 17.73 | 20.47 | 23.20 | 25.94 | 28.68 | 31.41 | 34.15 | 36.89 | | | | | | |
| 3.05 | 0.38 | 0.63 | 0.88 | 1.14 | 1.39 | 1.65 | 1.90 | 2.16 | 2.41 | 2.48 | 2.92 | 3.17 | 3.43 | | | | | | |

Document Links

[Architectural Louvers Catalog](#)

[Finishes & Colors](#)

[Qwik Ship Guide](#)

[Aiolite Warranty Statement](#)




K8506

Combination Louver/Damper | Drainable Blade | Extruded Aluminum

Airflow Resistance

Standard Air - 0.075 lb/ft³ (1.2 kg/m³)

Test size 48 in. x 48 in. (1219 mm x 1219 mm)




Model K8506 resistance to airflow (pressure drop) varies depending on louver application (air intake or air exhaust). Free area velocities (shown) are higher than average velocity through the overall louver size. See louver selection information. (Test Figure 5.5-6.5)

Water Penetration

Standard Air - 0.075 lb/ft³ (1.2 kg/m³)

Test size 48 in. x 48 in. (1219 mm x 1219 mm)

Test duration of 15 min.



The AMCA Water Penetration Test provides a method for comparing various louver models and designs as to their efficiency in resisting the penetration of rainfall under specific laboratory test conditions. The beginning point of water penetration is defined as that velocity where the water penetration curve projects through 0.01 oz. (3 g) of water (penetration) per sq. ft. (m²) of louver free area.

***The beginning point of water penetration for Model K8506 is 1035 fpm (5.258 m/s) free area velocity.**

These performance ratings do not guarantee a louver to be weatherproof or stormproof and should be used in combination with other factors including good engineering judgement in selecting louvers.

