



ARABIAN THERMAL AIRE INDUSTRIES
NEW RANGE OF TESTED & CERTIFIED
SOUND ATTENUATORS



Arabian Thermal Aire Industries PO Box 10125, Jubail Industrial City, Saudi Arabia-31961

Tel: +966133415857 Fax: +966133411631 email:info@ataiksa.com



Introduction:

ATAI is a leading manufacturer within the GCC for the supply of certified sound attenuators. This is achieved through professional engineer design, manufacturing and supply service that we provide to each of our clients, new and old.

This catalog will provide you with our range of ATAI, **Tested & Certified ARAMCO 9 COM** sound attenuator systems. These new attenuators are designed to achieve the required performances as set out in the ASTM Standards E477-06a for prefabricated attenuators.



“Arabian Thermal Aire Industries Co Ltd, certifies that the attenuators shown herein are licensed to bear the AMCA Seal. The rating shown are based on tests and procedures performed in accordance with AMCA Publication 1011 and comply with requirements of AMCA certified Rating Program. AMCA Certified Rating Seal applies dynamic insertion loss, airflow, generated noise and pressure drop”.

The following ATAI Sound Attenuator models enclosed within this document have been tested in accordance to **AMCA Certified Ratings Program and are licensed to bear the AMCA Seal.**

Manufacturing Process

Outer casings of rectangular silencer modules are constructed from of 22 gauge (0.8mm) galvanized steel in accordance with HVAC DW 144 recommended construction for high pressure rectangular duct-work. Seam shall be lock formed and mastic filled. Interior partitions for rectangular silencers shall be made of not less than 24 gauge (0.8mm) galvanized perforated steel. All splitters are aerodynamically bull nosed.

Infill Material

The infill material will be of inorganic mineral or glass fiber of a density sufficient to obtain the specified acoustic performance and be packed under not less than 5% compression to eliminate voids due to vibration and settling. Materials shall be inert, vermin and moisture proof.

Accessories

- | | |
|---|-----------------------------------|
| Slide on flanges | Integral inlet and outlet plenums |
| Casing thicknesses in a range of sizes | Fire Rated Silencers |
| Angle flanges | Bend Silencers |
| Vertical or horizontal splitter orientation | Cylindrical Silencers |
| Removable splitters | Crosstalk Silencers |
| Melinex wrapped infill Glass cloth wrapped infill | |



ATAI ASA A Model Dynamic insertion Loss ,dB

Model & Dimension	Silencer Face Velocity	Pressure Drop	Octave Band Centre Frequency(Hz)							
			63	125	250	500	1K	2K	4K	8K
WXHXL(mm)	M/S	Pa								
ASA 3A Model (600mm x 600mm x 900mm)	-7.62	299	4	8	14	24	32	26	19	14
	-5.08	134	3	7	16	27	33	25	21	19
	-2.5	32	4	9	20	26	32	25	19	15
	0	0	4	8	14	24	31	24	18	16
	2.5	32	3	8	17	24	30	24	20	18
	5.08	134	3	7	16	23	29	24	19	16
	7.62	299	2	7	16	22	28	24	21	19
ASA 4A Model (600mm x 600mm x 1200mm)	-7.62	299	5	11	21	37	39	31	19	12
	-5.08	134	5	10	20	36	42	30	20	14
	-2.5	32	4	9	20	35	45	29	19	15
	0	0	4	8	18	34	46	29	20	18
	2.5	32	3	8	17	32	45	30	20	18
	5.08	134	3	7	16	31	45	30	21	19
	7.62	299	2	7	16	30	39	30	21	19



ATAI ASA L Model Dynamic Sound Power ,dB										
Model & Dimension	Silencer Face Velocity	Pressure Drop	Octave Band Centre Frequency(Hz)							
WXHXL(mm)	M/S	Pa	63	125	250	500	1K	2K	4K	8K
ASA 3A Model (600mm x 600mm x 900mm)	-7.62	299	73	61	54	57	60	67	62	56
	-5.08	134	62	59	52	52	52	58	45	38
	-2.5	32	59	45	36	43	33	32	19	23
	2.5	32	59	45	36	36	33	25	19	23
	5.08	134	62	59	52	52	52	49	45	38
	7.62	299	74	70	63	62	61	60	58	54
ASA 4A Model (600mm x 600mm x 1200mm)	-7.62	299	73	61	54	57	60	67	62	56
	-5.08	134	61	51	47	51	58	57	50	43
	-2.5	32	61	44	42	46	40	31	21	24
	2.5	32	59	45	36	36	33	25	19	23
	5.08	134	62	59	52	52	52	49	45	38
	7.62	299	74	70	63	62	61	60	58	54



Face Area Adjustment factors						
Face area M2	0.5	1	2	4	6	16
L _w Adjustment Factor dB	-3	0	+3	+6	+9	+12


Attenuator model Diagram to be added

ATAI attenuators have been tested and certified following procedures in accordance with applicable sections of ASTM E477, 06a.

Dynamic Insertion Loss and Self-Noise Acoustic Performance Data were obtained in AMCA, USA test facility using the duct-to-room reverberant test facility with air flowing through the silencers.


Forward Flow (+) occurs when noise and air travel in the same direction, as in a typical supply or fan discharge system.

Reverse Flow (-) occurs when noise and air travel in opposite directions, as in a typical return or intake.





Aerodynamic Performance Data						
Model			Static pressure drop N/m²			
ASA 4A			30	134	299	548
Width	Height	Silencer Face Area (m²)	Air Flows , m³/s			
150	300	0.045	0.10	0.23	0.34	0.48
300	300	0.090	0.20	0.45	0.68	0.91
300	450	0.135	0.30	0.69	1.03	1.37
300	600	0.180	0.4	0.91	1.37	1.83
300	750	0.225	0.5	1.14	1.71	2.29
300	900	0.270	0.6	1.37	2.06	2.74
300	1050	0.315	0.7	1.6	2.4	3.2
300	1200	0.360	0.8	1.82	2.74	3.66
600	450	0.270	0.6	1.37	2.06	2.74
600	600	0.360	0.7	1.82	2.74	4.57
600	750	0.450	0.8	2.28	3.43	5.49
600	900	0.540	1.2	2.74	4.11	6.4
600	1050	0.630	1.7	3.2	4.8	7.32
600	1200	0.720	1.61	3.66	5.49	9.14
1200	750	0.900	2.01	4.57	6.86	10.97
1200	900	1.080	2.42	5.49	8.23	12.8
1200	1050	1.260	2.82	6.4	9.6	12.8
1200	1200	1.440	3.22	7.31	10.97	14.63
Static Face Velocity m/s			2.24	5.08	7.62	10.16





Arabian Thermal Aire Industries have a full range of HVAC & Noise control System, listed below are some of the system we provide;

HVAC & INDUSTRIAL AIR DISTRIBUTION SYSTEMS

- Duct (Rectangular, Spiral, Flat Oval & Flex Duct).
- Damper (Fire, Fire Smoke damper & Volume Control Damper)
- Louver (Stationary, Sandtrap, & Acoustic)
- Access Doors.

Noise & Vibration Control

- Acoustic Enclosures
- Acoustic/Noise Barriers
- Duct & Pipe Vibration isolation System.
- AHU, Fan, Generators, Chiller Vibration Isolation System.

Building Acoustic Systems

- Independent isolated wall system
- Resiliently Hung isolated Ceiling Systems.
- Floating Acoustic Floors
- Timber Acoustic Door & Glazed System.

Architectural Acoustic Systems


- Timber Wall & Ceiling Panel System.
- Fabric Wall & Ceiling Panel Systems.
- Acoustic Cloud Systems.
- Pro Audio Studio Acoustic Systems.

The ATAI product CD provides our full range of HVAC, Air Distribution and Noise Control system with Our technical specification for each System.

Business Card Pocket

Business Card Pocket

CD pocket for ATAI Full Product Range





Contact Information

Arabian Thermal Aire Industries



Head office Saudi Arabia

Address: P.O Box 10125
Jubail Industrial City
31961
Saudi Arabia
Phone: +966122415857
Email: info@ataiksa.com
Web: www.ataiksa.com

ATAIFzc



UAE Manufacturing Facility

Address; Technology Park
P.O Box 9746
Ras Al Khaimah
United Arab Emerites
+97172445977
info@ataifzc.com
www.ataifzc.com

Regional Offices

Riyadh
Ph: +966114761232

Jeddah
Ph:+966126532556

Bahrain
Ph:+97335427979



Certification



*ATAI ASA Attenuator Catalogue 0003 Edition
Date: December, 2021*

Arabian Thermal Aire Industries PO Box 10125, Jubail Industrial City, Saudi Arabia-31961
Tel: +966133415857 Fax: +966133411631 email: info@ataiksa.com