

Combination Fire/Smoke Damper • 1½ Hour Rated • Class II • 250°F or 350°F • Single Thickness Blades • Galvanized Steel

**Standard Construction and Materials****FRAME:** 20 GA. galvanized steel flat by 18" long integral sleeve.**BLADES:** 16 GA. galvanized steel single thickness, parallel action.**AXLES:** Plated solid steel stub.**BEARINGS:** Oil impregnated bronze.**LINKAGE:** Galvanized steel angle interconnect, with plated steel brackets and pivots located on blade.**STOPS:** 18 GA. galvanized steel at head and sill.**BLADE SEALS:** Silicone.**JAMB SEALS:** Stainless steel.**SLEEVE:** Integral 20 GA. galvanized steel by 18" long.**RETAINING ANGLES:** ¾" x 1½" x 16 GA. adjustable perimeter mounting angle.**CAULKING:** Hardcast Irongrip 601 or UL-listed equivalent.**FINISH:** Mill on galvanized steel.**ACTUATOR:** Electric with heat response device (EHRD) or pneumatic with heat response device (PHRD). Factory-installed for power-open/spring-close (fail close) operation. External left-hand mounted as viewed from jackshaft side of damper.**UNDERWRITERS LABORATORIES INC.®**  
CLASSIFIED DYNAMIC FIRE AND SMOKE DAMPER

FIRE RESISTANCE RATING 1½ HOUR

LEAKAGE RESISTANCE CLASS II



FILE # R6462



This combination fire/smoke damper meets the construction and performance requirements of:

- Underwriters Laboratories Inc. Standards 555 and 555S
- National Fire Protection Association Standards 80, 90A, 92, 101, 105
- ICC's International Building Code
- California State Fire Marshal Listing #3225-1328:120
- Underwriters Laboratories Inc. Approved for dual direction airflow and dynamic conditions.
- Underwriters Laboratories Inc. Classified for use in fire resistive ratings of less than 3 hours.
- Underwriters Laboratories Inc. Classified for use in smoke control systems for Leakage Class II and 250°F or 350°F.
- Actuators must be arranged to operate automatically, must fail closed upon loss of power, and must be controlled by a smoke detection system.

**Options**

Integral Dual Position Indication (IDPI) switches

Sensotherm re-openable heat response device (ESOT) for electric actuator

Sensotherm re-openable heat response device (PSOT) for pneumatic actuator

Model SM-501 Flow-rated smoke detector ship loose

Model SM-501 Flow-rated smoke detector mounted and wired (6" minimum damper height with a 20" sleeve - extra 2" on jackshaft side)

Tab-Lock retaining angles

Stainless steel bearings

Copper tubing (for pneumatic actuators)

Optional 19" or 20" sleeve depth - Additional sleeve length is added to non-jackshaft side unless ordered with mounted smoke detector and/or less than 6"H with B-Pan Transition

Round or oval transitions


Short-width (less than 6") and/or short-height (less than 6") transitions

**Notes**

1. "A" width and "B" height are opening dimensions. Damper frames are provided approximately ¼" undersized.
2. Dampers are available in 1" increments only.
3. Dampers for horizontal installation can only be mounted in a fire barrier constructed of masonry/concrete materials.
4. The blades must stay in the fire wall. The adjustable retaining angle may only be adjusted the distance shown on the label or installation instructions.

**Damper Sizes**

Orientation	Horizontal & Vertical	
	Minimum Panel	Maximum Panel
Rectangular	4"W x 4"H (6"W x 6"H frame)	18"W x 18"H
Round	4" dia. (6"W x 6"H frame)	16" dia.
Oval	4"W x 4"H (6"W x 6"H frame)	16"W x 16"H



\*Dampers smaller than minimum frame size require a transition. Reference SD-TRFS. Dampers less than 6"H will have a 20" sleeve with the additional sleeve length on the jackshaft side when a B-Pan type transition is ordered.

Combination Fire/Smoke Damper • 1½ Hour Rated • Class II • 250°F or 350°F • Single Thickness Blades • Galvanized Steel

### Operations Ratings

Maximum Differential Pressure: 4 in. w.g.  
Maximum Velocity: 2000 fpm

### Leakage Ratings

UL Class II  
20 cfm per sq. ft. maximum @ 4 in. w.g.

### Sound Ratings

The Noise Criterion data below was tested in accordance with ASTM E477.99 in the center octave band.

Noise Criterion (NC)				
Damper Size	Velocity fpm (m/s)			
	1000 (5.08)	2000 (10.16)	3000 (15.24)	4000 (20.32)
12"W x 12"H (305mm x 305mm)	22dB	44dB	55dB	62dB

### Pressure Drop Ratings

The pressure drop data shown below is based on laboratory conditions. The test setup does not take into account elbows or other duct fittings that are part of every actual duct system. The configuration of the actual duct system immediately upstream and downstream of the damper often contributes more pressure loss than the damper itself.

#### 12"W x 12"H

Velocity (FPM)	ΔP (in. w.g.)
500	0.01
1000	0.04
1500	0.09
2000	0.16
2500	0.25

#### 24"W x 24"H

Velocity (FPM)	ΔP (in. w.g.)
500	0.01
1000	0.04
1500	0.08
2000	0.15
2500	0.23

This damper tested in accordance with AMCA 500-D, Figure 5.3

Intake air converted to standard air density.



Cesco Products certifies that the model CR2 damper shown here is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to Air Performance Ratings only.

Item #	Qty	Damper Size	Horizontal	Vertical	250°F	350°F			
			Orientation		Air Temp. Rating		Union Made		
Arch. / Eng.:			EDR:		ECN:		Job:		
Contractor:									
Project:			Date:		DWN:		DWG:		