



*Hunter*



ASSEMBLED WITH CARE IN  
NASHVILLE, TENNESSEE

# XP PERFORMANCE



Hunter Industrial certifies that the model XP shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

The AMCA Certified Ratings Program seals applies to airflow rate and power rating free delivery only.

Performance ratings do not include the effects of appurtenances.

No part of this document may be reproduced or translated into a different language or format without the prior written consent of Hunter Fan Company. The information contained in this document is subject to change without notice.

DIAMETER	INPUT POWER	% OF FULL SPEED	SPEED (RPM)	POWER (W)	AIR FLOW (CFM)	STANDBY POWER (W)	CFEI 100% (≥ 1.00)	CFEI 40% (≥ 1.31)
14 ft XP	100-120V, 1Φ	100%	108	723	85,466	13.3	1.26	2.17
		80%	87	370	68,616			
		60%	65	180	51,507			
		40%	44	85	34,556			
		20%	22	53	17,431			
12 ft XP	100-120V, 1Φ	100%	106	786	68,675	13.2	1.15	1.87
		80%	85	397	54,317			
		60%	64	198	39,829			
		40%	43	92	26,451			
		20%	22	54	13,345			
10 ft XP	100-120V, 1Φ	100%	139	821	55,106	13.3	1.22	1.87
		80%	111	410	43,650			
		60%	84	196	32,831			
		40%	56	101	21,958			
		20%	28	56	10,928			
8 ft XP	100-120V, 1Φ	100%	156	474	34,131	13.2	1.53	2.07
		80%	125	267	27,489			
		60%	94	147	20,608			
		40%	63	79	13,944			
		20%	32	52	7,262			

Fans tested in forward direction of operation.

All fans have 10 speeds for forward and reverse operation.

Fans can also operate in the reverse direction in the wintertime for destratification.



Headquarters:

180 Threet Industrial Road Suite 120  
Smyrna, TN 37167  
[industrialfans.hunterfan.com](http://industrialfans.hunterfan.com)

Mexico Office:

Av. Eugenio Garza Lagüera 4001  
Monterrey, NL 64909  
[hunterfan.com.mx/pages/industrial](http://hunterfan.com.mx/pages/industrial)