



ARCHITECTURAL ELITE 8

Hot Water Heated Air Curtain

Data Sheet

For Mounting Heights To 8' (environmental separation)

STANDARD CONSTRUCTION

- 11" high x 23" deep
- 1/5 hp EC motor(s)
- Intelliswitch™ digital controller - ten speeds
- Berner AIR™ (smart controller & app) includes BACnet
- Cabinet: Brushed Stainless Steel, Grade 304 or better
- Bottom Panel: Clear satin anodized aluminum (Optional: White Aluminum, Custom Color or Stainless)
- Wall or Top Mounting
- High efficiency, low noise, articulating Pro-V Nozzle
- Filter (washable)
- Factory installed coil
- Optional: Rear cover for top mounting to conceal fasteners

Energy Codes ASHRAE 90.1-2019, IECC 2018, and ASHRAE 189.1 vestibule exception validated by AMCA certification. Refer to Velocity Projection Chart below for information.



Berner International certifies that the air curtains shown here in are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (hot water heated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

2 Year Limited Warranty



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Coil Output (MBH)	Entering / Leaving Water Temp. (°F)	Water Flow (GPM)	Fluid Pressure Drop (FT. WG.)	Air Temp. Rise (°F)	Net Wt. (lbs)
AE08-E-1036W	36.00	2,245	1,584	891	52%	0.24	1 @ 1/5	27.4	180° / 166°	4.0	1.3	28°	72
AE08-E-1042W	42.00	2,150	1,641	1,077	54%	0.30	1 @ 1/5	33.8	180° / 166°	5.0	2.1	29°	82
AE08-E-1048W	48.00	2,228	1,681	1,261	58%	0.34	1 @ 1/5	38.8	180° / 164°	5.0	2.1	28°	91
AE08-E-1060W	60.00	2,175	1,582	1,483	53%	0.42	1 @ 1/5	46.7	180° / 161°	5.0	2.2	29°	111
AE08-E-1072W	72.00	1,865	1,767	1,988	75%	0.47	1 @ 1/5	61.8	180° / 162°	7.0	4.4	28°	133
AE08-E-2084W	84.00	2,150	1,641	2,154	54%	0.60	2 @ 1/5	69.0	180° / 160°	7.0	4.6	29°	160
AE08-E-2096W	96.00	2,228	1,681	2,522	58%	0.68	2 @ 1/5	82.4	180° / 161°	9.0	7.8	30°	180
AE08-E-2108W	108.00	2,228	1,626	2,744	53%	0.76	2 @ 1/5	90.4	180° / 159°	9.0	8.0	30°	199
AE08-E-2120W	117.00	2,175	1,622	2,966	53%	0.84	2 @ 1/5	98.9	180° / 160°	10.0	10.1	30°	214

See sheet EP-226E for amp draws/total load requirements.

600/3/60 & 277/1/60 power supplies include extended cabinet, See drawing AE08-E-HW-TR.

NOTES:

- Standard connection top, same end supply/return.
- Coil should be field supplied with a solenoid valve that energizes only when air curtain is energized. Consideration must be taken for freeze protection when necessary.
- Coil performance based on 65°F entering air temperature.
- Maximum leaving air temperature shall not exceed 120F.
- Consult factory for alternate entering air & water temperatures or GPM's.

MODEL NUMBER CONFIGURATION

AE08-E-1 036 W A-EC-WCA -TB-LL-SA

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Control	Opt. Display	Supply/Return	Material/Finish	
										Cabinet	Bottom Panel
AE08	E	1, 2	036" - 120"	W=Hot Water Heated	A=120/1/60* B=208/1/60 J=240/1/60 V=220/1/50 W=277/1/60 † A-XI=600/3/60 †	EC Motor	WCA= Berner AIR™ smart control	Remote Touchscreen	LL=Left Hand RR=Right Hand	S=Stainless (std) A= Anod Alum C=Custom Color	A=Anod Alum (std) S=Stainless C=Custom Color

*Suitable for 50hz
† Add 5" to cabinet width for transformer

VELOCITY PROJECTION: Model AE08-E-1036W

	40	80	120
Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	1308	957	772
Uniformity (%)	68%	85%	90%

Sound level measured 10' (3m) from the unit in free field:

- 1 motor: Min./Max. Speed: 50/53 dBA
- 2 motors: Min./Max. Speed: 50/53 dBA

Sound data is not AMCA certified.

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (2.0 m/s; 400 fpm) at 6.0 in (15 cm) above the floor."

Berner reserves the right to alter specifications without prior notice.