



ARCHITECTURAL ICON 8

Ambient (Unheated) Air Curtain

Data Sheet

Recommended for Mounting Heights to 8' (environmental separation) and 7' (insect control)

STANDARD CONSTRUCTION

- 8 1/4" high x 16" deep
- 1/5 hp motor(s) - ten speeds
- Factory installed Intelliswitch™ digital controller
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Filter (washable)

OPTIONS

- 1/5 hp EC motor(s) - ten speeds
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners
- Berner AIR™ (smart controller & app, includes BACnet)

Energy Codes ASHRAE 90.1-2019, IECC 2018, and ASHRAE 189.1 vestibule exception validated by AMCA certification. Refer to Velocity Projection Chart below for information.



Berner International certifies that the air curtains shown here-in are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year
Limited
Warranty



indoor use



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
AI08-E-1036A	36.00	2,308	1,758	989	85%	0.21	1 @ 1/5	48
AI08-E-1042A	42.00	2,425	1,778	1,167	83%	0.24	1 @ 1/5	53
AI08-E-1048A	48.00	2,417	1,827	1,370	80%	0.26	1 @ 1/5	58
AI08-E-1060A	59.00	2,276	1,827	1,684	81%	0.33	1 @ 1/5	69
AI08-E-1072A	72.00	2,185	1,648	1,854	84%	0.35	1 @ 1/5	79
AI08-E-2078A	78.00	2,425	1,769	2,156	83%	0.44	2 @ 1/5	96
AI08-E-2084A	84.00	2,425	1,778	2,334	83%	0.47	2 @ 1/5	106
AI08-E-2096A	96.00	2,417	1,827	2,740	80%	0.53	2 @ 1/5	116
AI08-E-2108A	108.00	2,417	1,810	3,054	80%	0.60	2 @ 1/5	127
AI08-E-2120A	118.00	2,276	1,827	3,368	81%	0.67	2 @ 1/5	138

See sheets EP-280E-AC & EP-280E-EC for amp draws/total load requirements.
600/3/60 power supply includes transformer housing, See drawing AI08-E-AMB-600

NOTE: Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

MODEL NUMBER CONFIGURATION

AI08-E-1 036 A A-AC-WCA -SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Opt. Control	Opt. Cabinet Finish
AI08	E	1, 2	036" - 120"	A=Ambient	AC & EC motors A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 220/1/50 A-XI = 600/3/60 † EC motors only W = 277/1/60	AC= Standard Motor EC= Optional Motor	WCA= Berner AIR™ smart control	SS=Stainless Steel CC=Custom Color

*Suitable for 50 Hz
† Add 5" for transformer housing

for Standard offering, leave options (Opt.) blank

Sound level measured 10' (3m) from the unit in free field:

1 motor: Min./Max. Speed: 49/55 dBA

2 motors: Min./Max. Speed: 52/58 dBA

Sound data is not AMCA certified.

VELOCITY PROJECTION: Model AI08-E-1036A			
Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	874	766	576
Uniformity (%)	90%	88%	87%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Berner reserves the right to alter specifications without prior notice.

www.berner.com Berner International 800.245.4455
111 Progress Ave. / New Castle / PA / 16101 / USA

DS-280E
December, 2024

©Copyright, 2024 Berner International