



# ARCHITECTURAL ICON 8

## Hot Water Heated Air Curtain

### Data Sheet

Recommended for Mounting Heights to 8' (environmental separation) and 7' (insect control)

#### STANDARD CONSTRUCTION

- 8 1/4" high x 16" deep
- 1/5 hp motor(s) - ten speeds
- Factory installed Intelliswitch™ digital controller
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Factory installed coil
- Filter (washable)

#### OPTIONS

- 1/5 hp EC motor(s) - ten speeds
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners
- Berner AIR™ (smart controller & app, includes BACnet)

Energy Codes ASHRAE 90.1-2019, IECC 2018, and ASHRAE 189.1 vestibule exception validated by AMCA certification.  
Refer to Velocity Projection Chart below for information.



Berner International certifies that the air curtains shown here-in are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (hot water heated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

2 Year  
Limited  
Warranty



indoor use



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Coil Output (MBH)	Entering / Leaving Water Temp. (°F)	Water Flow (GPM)	Fluid Pressure Drop (FT. WG.)	Air Temp. Rise (°F)	Net Wt. (lbs)
AI08-E-1036W	36.00	2,054	1,545	869	84%	0.19	1 @ 1/5	27.1	180° / 166°	4.0	1.3	29°	68
AI08-E-1042W	42.00	1,985	1,547	1,015	82%	0.20	1 @ 1/5	32.9	180° / 166°	5.0	2.1	30°	76
AI08-E-1048W	48.00	2,013	1,585	1,189	80%	0.23	1 @ 1/5	37.9	180° / 164°	5.0	2.1	29°	83
AI08-E-1060W	59.00	2,040	1,552	1,431	80%	0.26	1 @ 1/5	46.0	180° / 161°	5.0	2.2	29°	99
AI08-E-1072W	72.00	1,928	1,394	1,568	83%	0.28	1 @ 1/5	55.8	180° / 164°	7.0	4.4	32°	117
AI08-E-2078W	78.00	2,054	1,546	1,884	82%	0.39	2 @ 1/5	62.8	180° / 162°	7.0	4.5	30°	136
AI08-E-2084W	84.00	1,985	1,547	2,030	82%	0.41	2 @ 1/5	67.3	180° / 160°	7.0	4.6	30°	149
AI08-E-2096W	96.00	2,013	1,585	2,378	80%	0.46	2 @ 1/5	80.4	180° / 162°	9.0	7.8	31°	164
AI08-E-2108W	108.00	2,040	1,553	2,620	80%	0.49	2 @ 1/5	88.6	180° / 160°	9.0	8.0	31°	180
AI08-E-2120W	118.00	2,040	1,552	2,862	80%	0.53	2 @ 1/5	97.8	180° / 160°	10.0	10.1	31°	195

See sheets EP-286E-AC & EP-286E-EC for amp draws/total load requirements.

600/3/60 power supply includes transformer housing, See drawing AI08-E-WTR-600

#### NOTES:

1. Standard connection same end supply/return.
2. Coil should be field supplied with a solenoid/control valve that energizes only when air curtain is energized.  
Consideration must be taken for freeze protection when necessary.
3. Coil performance based on 65°F entering air temperature.
4. Maximum leaving air temperature shall not exceed 120°F.
5. Consult factory for alternate entering air & water temperatures or GPM's.
6. Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

## MODEL NUMBER CONFIGURATION

AI08-E-1 036 W A-AC-WCA -SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Opt. Control	Opt. Cabinet Finish
AI08	E	1, 2	036" - 120"	W=Hot Water Heated	<b>AC &amp; EC motors</b> A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 220/1/50 A-XI = 600/3/60 † <b>EC motors only</b> W = 277/1/60	AC= Standard Motor EC= Optional Motor	WCA= Berner AIR™ smart control	SS=Stainless Steel CC=Custom Color

for Standard offering, leave options (Opt.) blank

\*Suitable for 50 Hz  
† Add 5" for transformer housing

Sound level measured 10' (3m) from the unit in free field:

1 motor: Min./Max. Speed: 50/55 dBA

2 motors: Min./Max. Speed: 53/58 dBA

Sound data is not AMCA certified.

VELOCITY PROJECTION: Model AI08-E-1036W			
Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	859	588	547
Uniformity (%)	89%	87%	91%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Berner reserves the right to alter specifications without prior notice.

www.berner.com Berner International 800.245.4455  
111 Progress Ave. / New Castle / PA / 16101 / USA

DS-286E  
December, 2024