



ARCHITECTURAL ICON 10

Ambient (Unheated) Air Curtain

Data Sheet

Recommended for Mounting Heights to 10' (environmental separation) and 8' (insect control)

STANDARD CONSTRUCTION

- 12 ¾" high x 22" deep
- 1/2 hp motor(s) - ten speeds
- Factory installed Intelliswitch™ digital controller
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Filter (washable)

OPTIONS

- 1/2 hp EC motor(s) - ten speeds
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners
- Berner AIR™ (smart controller & app, includes BACnet)

Energy Codes ASHRAE 90.1-2019, IECC 2018, and ASHRAE 189.1 vestibule exception validated by AMCA certification.

Refer to Velocity Projection Chart below for information.



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year Limited Warranty



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
AI10-E-1036A	36.00	3,440	2,071	1,424	80%	0.51	1 @ ½	85
AI10-E-1042A	42.00	3,711	1,849	1,483	82%	0.52	1 @ ½	94
AI10-E-1048A	48.00	3,975	1,973	1,809	92%	0.63	1 @ ½	110
AI10-E-1060A	59.00	3,803	1,619	1,824	82%	0.61	1 @ ½	119
AI10-E-2072A	72.00	3,440	2,071	2,848	80%	1.02	2 @ ½	170
AI10-E-2084A	84.00	3,711	1,849	2,966	82%	1.04	2 @ ½	188
AI10-E-2096A	96.00	3,975	1,973	3,618	92%	1.26	2 @ ½	220
AI10-E-2108A	108.00	3,975	1,761	3,633	82%	1.24	2 @ ½	229
AI10-E-2120A	118.00	3,803	1,619	3,648	82%	1.22	2 @ ½	238
AI10-E-3132A	132.00	3,975	2,000	5,042	80%	1.77	3 @ ½	305
AI10-E-3144A	144.00	3,975	1,973	5,427	92%	1.89	3 @ ½	330


See sheets EP-290E-AC & EP-290E-EC for amp draws/total load requirements.

600/3/60 power supply includes extended cabinet, See drawing AI10-E-AMB-600

NOTE: Operation of AC motor at 50Hz will generate a 17% reduction in performance; no reduction for EC motors.

MODEL NUMBER CONFIGURATION

AI10-E-1 036 A A-AC-WCA -SS



for Standard offering, leave options (Opt.) blank

*Suitable for 50 Hz
 † Cabinet width increases for transformer

Sound level measured 10' (3m) from the unit in free field:

1 motor: Min./Max. Speed: 53/56 dBA
 2 motors: Min./Max. Speed: 56/59 dBA
 3 motors: Min./Max. Speed: 59/61 dBA

Sound data is not AMCA certified.

VELOCITY PROJECTION: Model AI10-E-1036A				
Distance from Nozzle (in)	40	80	120	160
Core Velocity (fpm)	1454	971	918	748
Uniformity (%)	88%	91%	92%	95%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Berner reserves the right to alter specifications without prior notice.

www.berner.com Berner International 800.245.4455
 111 Progress Ave. / New Castle / PA / 16101 / USA

DS-290E
 June, 2023