



K Circular Duct Fans

High Quality radial fan for circular ducts

- Available with AC and EC motors
- Indoor and outdoor installation
- Reliable and airtight
- Mounting bracket included
- Noise and energy optimized impeller

[Find more details in our online catalogue.](#)

Flexibility

The K fans are intended to use for **supply** or **extract** air, designed to be installed in **any position**. This ensures that the fans can be used in a variety of **commercial** and **domestic** applications.

Reliability

The unit's **airtight casing** and corrosion resistance permits **outdoor** and **indoor** use. The combination of reliable casing and motor construction ensures, to minimize the need for maintenance of the fans and allows long **continuous operation**.

Performance

Sound optimized radial impeller together with **high efficient** external rotor motor are designed to ensure high-level performance to **minimize power consumption** and **maximize efficiency**.

Accessories

K fans can be selected together with variety types of **accessories** as fast clamps, heaters, filters, dampers, etc.

Certifications



Ecodesign (ErP) compliant

Compliant with today's and tomorrow's European Union rules and requirements for energy labelling and ecodesign for Energy-related Products (ErP).

Features

Construction

Casing made of **galvanised sheet steel**, corrosion **class C3** is fully **air tight class C** according to EN1751. The fans are equipped with an external **terminal box with** protection class **IP55**.

Impeller

K fans use backward curved **radial** impellers. These are from lightweight, hard-wearing fiberglass reinforced **polyamide**, dynamically **balanced** and paired with corresponding external rotor motors.

Motor

Depending on type, K fans are equipped with **AC** or high efficient **EC** external rotor motors. All motors are suitable for **50Hz** and **60Hz**.

Motor protection

Fans with **AC** motors have **integrated** thermal protection with manual (electrical) reset. Size 100 and 125 has an impedance motor protection.

Fans with **EC** motors have an **integrated** electronic **thermal protection** including **locked-rotor protection** and **soft-start**.

Control

EC motor with **built-in potentiometer** to adjust working point can be also controlled by external **signal 0-10V**.

AC motor can be controlled by **5-step** or **stepless** speed regulator.

Installation

K fans can be installed in **any** position **indoor** and **outdoor** by included **mounting brackets**. All models have a spigot with 25 mm length which is perfectly designed to connect circular duct by **fast clamps preventing vibration** to the duct. Installation can be combined with filter boxes, sound attenuators, and other mechanical accessories from recommended list.

Technical parameters

Nominal data

Voltage (nominal)	230	V
Frequency	50	Hz
Phases	1~	
Input power	29	W
Input power kW	0.029	kW
Input current	0.164	A
Impeller speed	2,488	rpm
Air flow	max 187	m³/h
Temperature of transported air	max 70	°C
Max temperature of transported air, when speed controlled	70	°C

Sound data

Sound pressure level at 3m (20m² Sabin)	36	dB(A)
---	----	-------

Protection/Classification

Enclosure class, motor	IP44
Insulation class	B

Data according to ErP

Energy class, Basic unit	F
Energy class, Local demand	C
ErP ready	ErP 2018

Dimensions and weights


Duct dimension; Circular, inlet	125	mm
Duct dimension; Circular, outlet	125	mm
Weight	2.3	kg

Others

Duct connection type	Circular
Motor type	AC

Performance

Performance curve



Performance certified is for installation type D – Ducted inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Values shown are for inlet Lwi and LwiA and outlet Lwo and LwoA sound power levels for installation type D: ducted inlet, ducted outlet. Ratings include the effects of duct end correction. The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. The sound power level ratings shown are in decibels, referred to 10⁻¹² watts, calculated per AMCA International Standard 301. AMCA certified data is, Airflow, Static pressure, Power, Inlet sound, Outlet sound at 230V

Hydraulic data

Required air flow	101 m³/h
Required static pressure	101 Pa
Working air flow	102 m³/h
Working static pressure	101 Pa
Air density	1.204 kg/m³
Power	27.7 W
Fan control - RPM	2,520 rpm
Current	0.16 A
SFP	0.982 kW/m³/s
Control voltage	230.0 V
Supply voltage	230 V

Sound power level		63	125	250	500	1k	2k	4k	8k	Total
Inlet	dB(A)	47	57	57	58	53	49	33	25	63
Outlet	dB(A)	48	58	53	54	49	47	36	27	61
Surrounding	dB(A)	28	32	30	39	37	32	21	18	43
Sound pressure level at 3m (20m² Sabine)	dB(A)	-	-	-	-	-	-	-	-	36
Sound pressure level at 3m free field	dB(A)	-	-	-	-	-	-	-	-	22

Certifications



[AMCA Worldwide Certified Ratings: Sound and Air Performance](#)

Systemair Production AB certifies that the model K 125 M Sileo is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

Check the AMCA Certified and Listed Product Search for our products
<https://www.amca.org/certify/#certified-product-search>