


RSVOLUTION° 150 SERIES PERFORMANCE CATALOG





Rite-Hite Engineered Solutions Group certifies that the fan models 20'-24' shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

The AMCA Certified Ratings Seals applies to air performance ratings only. The AMCA Certified Ratings Seal applies at free delivery only. Performance ratings do not include the effects of appurtenances (accessories).

No part of this document may be reproduced or translated into a different language without the prior written consent of Rite-Hite. The information contained in this document is subject to change without notice.



24 ft (7.3 m) Diameter

400-480V, 3	400-480V, 3Ф, 60 Hz				
Fan Speed	Power	Airflow			
(RPM)	(W)	(CFM)	CFM/W	CFEI*	
53	1471	232890	158	1.18	
42	741	185485	250	1.38	
32	326	140195	430	1.76	
21	134	93532	698	2.18	
11	98	38606	406	1.36	

200-240V, 1	00-240V, 1Ф, 60 Hz				
Fan Speed	Power	Airflow			
(RPM)	(W)	(CFM)	CFM/W	CFEI*	
53	1471	228814	168	1.22	
42.5	680	183024	269	1.46	
32	294	139958	487	1.99	
21	109	94313	869	2.71	
11	71	54987	778	2.28	
Chandley Dayson C. Matte					

Standby Power: 7 Watts

Standby Power: 8 Watts

200-240V, 1Φ, 60 Hz

20 ft (6.1 m) Diameter

400-480V, 3	Ф, 60 Hz			
Fan Speed	Power	Airflow		
(RPM)	(W)	(CFM)	CFM/W	CFEI*
68	1852	201358	109	1.19
55	950	160018	169	1.33
41	403	118460	294	1.62
27	157	79249	504	2.00
14	102	36973	371	1.34

, , ,				
Fan Speed	Power	Airflow		
(RPM)	(W)	(CFM)	CFM/W	CFEI*
68	1672	192439	115	1.18
56	832	151737	182	1.34
41.5	356	112424	316	1.64
27.5	131	74327	568	2.17
14	69	34585	523	1.91

Standby Power: 8 Watts

Standby Power: 7 Watts

^{*}Ceiling Fan Energy Index (CFEI) based on Ansi/AMCA Standard 208 and 10 CFR 430

^{**}Fans tested in forward direction of operation.