


Vestibule Exception Compliance: up to 14 ft. AFF / Optimal Environmental Separation: up to 10 ft. AFF



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year Limited Warranty



indoor use



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
AC10-F-1036A	36.00	3,440	2,071	1,424	80%	0.51	1 @ ½	82
AC10-F-1042A	42.00	3,711	1,849	1,483	82%	0.52	1 @ ½	91
AC10-F-1048A	48.00	3,975	1,973	1,809	92%	0.63	1 @ ½	107
AC10-F-1060A	59.00	3,803	1,619	1,824	82%	0.61	1 @ ½	116
AC10-F-2072A	72.00	3,440	2,071	2,848	80%	1.02	2 @ ½	164
AC10-F-2078A	78.00	3,711	1,952	2,907	80%	1.03	2 @ ½	164
AC10-F-2084A	84.00	3,711	1,849	2,966	82%	1.04	2 @ ½	182
AC10-F-2096A	96.00	3,975	1,973	3,618	92%	1.26	2 @ ½	214
AC10-F-2108A	108.00	3,975	1,761	3,633	82%	1.24	2 @ ½	223
AC10-F-2120A	118.00	3,803	1,619	3,648	82%	1.22	2 @ ½	232
AC10-F-3132A	132.00	3,975	2,000	5,042	80%	1.77	3 @ ½	296
AC10-F-3144A	144.00	3,975	1,973	5,427	92%	1.89	3 @ ½	321

See sheets EP-270E-AC & EP-270E-EC for amp draws/total load requirements.

600/3/60 power supply includes extended cabinet, See drawing AC10-F-AMB-600

NOTE: Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

MODEL NUMBER CONFIGURATION

AC10-F-1 036 A A-AC-CB-D-R-SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Berner AIR	Opt. Data Link	Opt. Display	Opt. Cabinet Finish
AC10	F	1, 2, 3	036" - 144"	A=Ambient	AC & EC motors A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 230/1/50 A-XI = 600/3/60 † W = 277/1/60	AC (Std.) EC (Opt.)	CB=BASIC (Std.) CM=BMS (Opt.)	D=Physical Interconnect (daisy chain)	R=Remote Display TB=Tablet	SS=Stainless Steel CC=Custom Color

STANDARD CONSTRUCTION

- 12 ¾" high x 25 ¾" deep
- 1/2 hp AC motor(s) - ten speeds
- Touchscreen interface with Intelliswitch™ digital controller, includes Berner AIR® BASIC (smart control)
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Filter (washable)

OPTIONS

- 1/2 hp EC motor(s) - ten speeds
- Berner AIR® BMS (smart control with BACnet and Modbus capabilities)
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners

*Suitable for 50 Hz
† Add 12" to cabinet width for transformer

for Standard offering, leave options (Opt.) blank

VELOCITY PROJECTION: Model AC10-F-1036A				
Distance from Nozzle (in)	40	80	120	160
Core Velocity (fpm)	1454	971	918	748
Uniformity (%)	88%	91%	92%	95%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Sound level measured 10' (3m) from the unit in free field:

1 motor: Min./Max. Speed: 53/56 dBA
2 motors: Min./Max. Speed: 56/59 dBA
3 motors: Min./Max. Speed: 59/61 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.