



ARCHITECTURAL ICON 8

Steam Heated Air Curtain

Data Sheet

Recommended for Mounting Heights to 8' (environmental separation) and 7' (insect control)

Vestibule Exception for Energy Codes ASHRAE 90.1-2019, IECC 2018, and ASHRAE 189.1, validated by AMCA certification.

VELOCITY PROJECTION: Model AI08-F-1036S

Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	859	588	547
Uniformity (%)	89%	87%	91%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with the AMCA Certified Ratings Program. Rated data shown is for base (steam heated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

**2 Year
Limited
Warranty**



indoor use



MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Coil Output (MBH)	Inlet Pressure (PSIG)	Condensate (lbs/hr)	Air Temp. Rise (°F)	Net Wt. (lbs)
AI08-F-1036S	36.00	2,054	1,545	869	84%	0.19	1 @ 1/5	44.5	5	45.8	47°	68
AI08-F-1042S	42.00	1,985	1,547	1,015	82%	0.20	1 @ 1/5	52.4	5	54.0	48°	76
AI08-F-1048S	48.00	2,013	1,585	1,189	80%	0.23	1 @ 1/5	61.1	5	62.9	47°	83
AI08-F-1060S	59.00	2,040	1,552	1,431	80%	0.26	1 @ 1/5	75.6	5	77.9	49°	99
AI08-F-1072S	72.00	1,928	1,394	1,568	83%	0.28	1 @ 1/5	87.1	5	89.8	51°	117
AI08-F-2078S	78.00	2,054	1,546	1,884	82%	0.39	2 @ 1/5	99.8	5	102.9	49°	136
AI08-F-2084S	84.00	1,985	1,547	2,030	82%	0.41	2 @ 1/5	107.7	5	111.0	49°	149
AI08-F-2096S	96.00	2,013	1,585	2,378	80%	0.46	2 @ 1/5	125.1	5	128.9	49°	164
AI08-F-2108S	108.00	2,040	1,553	2,620	80%	0.49	2 @ 1/5	139.6	5	143.8	49°	180
AI08-F-2120S	118.00	2,040	1,552	2,862	80%	0.53	2 @ 1/5	152.1	5	156.7	49°	196

See sheets EP-284E-AC & EP-284E-EC for amp draws/total load requirements.

600/3/60 power supply includes transformer housing, See drawing AI08-F-STM-600

NOTES:

- Standard connection same end supply/return.
- Coil should be field supplied with a solenoid/control valve that energizes only when air curtain is energized. Consideration must be taken for freeze protection when necessary.
- Coil performance based on 65°F entering air temperature.
- Maximum leaving air temperature shall not exceed 120°F.
- Consult factory for alternate steam pressures.
- Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

MODEL NUMBER CONFIGURATION

AI08-F-1 036 S A-AC-CB-D-R-SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Berner AIR	Opt. Data Link	Opt. Display	Opt. Cabinet Finish
AI08	F	1, 2	036" - 120"	S=Steam Heated	AC & EC motors A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 220/1/50 A-XI = 600/3/60 † EC motors only W = 277/1/60	AC (Std.) EC (Opt.)	CB=BASIC (Std.) CM=BMS	D=Physical Interconnect (daisy chain)	R=Remote Display TB=Tablet	SS=Stainless Steel CC=Custom Color

STANDARD CONSTRUCTION

- 8 1/4" high x 16" deep
- 1/5 hp motor(s) - ten speeds
- Intelliswitch™ digital controller, includes Berner AIR® BASIC (smart control)
- Clear satin anodized aluminum exterior
- Wall or Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Factory installed coil
- Filter (washable)

OPTIONS

- 1/5 hp EC motor(s) - ten speeds
- Custom Color or Stainless
- Rear cover for top mounting to conceal fasteners
- Berner AIR® BMS (smart control with BACnet and Modbus capabilities)

for Standard offering, leave options (Opt.) blank

Sound level measured 10' (3m) from the unit in free field:

1 motor: Min./Max. Speed: 50/55 dBA

2 motors: Min./Max. Speed: 53/58 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.

www.berner.com Berner International 800.245.4455
111 Progress Ave. / New Castle / PA / 16101 / USA

DS-284E
January, 2025