

RS-5605

Material

- Material: aluminium alloy 6063-T6
- Nominal thickness: 1.52 mm for blades; 2.03 mm for head and cill frames; 3.18 mm for jamb frames and mullions
- Optional extras: bird/vermin guards, insect mesh, blanking plates, insulated blanking panels, cill pans and integrated glazing frames

Test Summary


Tested with mill finish and no accessories.

For a 1220 mm x 1220 mm (4' x 4') unit.

- Free area = 0.88 m² (9.46 ft²)
- Percent free area = 59.2%
- Intake Pressure Drop at 5.08 m/s (1,000 FPM) free area velocity = 24.8 Pa (0.10 in. H₂O)

For a unit with 1m² core area.

- To maintain a CLASS A (99%) effectiveness rating* with:
 - a 22.3 m/s (50 mph) wind speed and rainfall rate of 203 mm/hr (8 in/hr)
 - Max. intake core velocity 5.00 m/s (984 FPM)
 - Max. intake free area velocity 7.62 m/s (1500 FPM)



Discharge Coefficient (C_d)

Intake = 0.53 (Class 1), Exhaust = 0.46 (Class 1)
AMCA certifies the coefficient class only



Construction Specialties UK Ltd certifies that the louvre model RS-5605 shown herein is licensed to bear the AMCA Seal.

The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to Wind-Driven Rain and Air Performance ratings.




Wind-Driven Rain Performance

Tested with 1m² core area, mill finish and no accessories*

22.3 m/s (50 mph) & 203 mm (8") rain per hour

Core Velocity Through Calibration Plate (m/s):	0.0	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0
Free Area Velocity (m/s):	0	0.76	1.52	2.29	3.05	3.81	4.58	5.34	6.10	6.86	7.62
Rating Effectiveness:	A	A	A	A	A	A	A	A	A	A	A
Effectiveness Ratio (%):									100	99.9	99.9
Effectiveness Rating:	A = 1 to 0.99			B = 0.989 to 0.95			C = 0.949 to 0.80			D = Below 0.80	

RS-5605



Data corrected to standard air density.
1220 mm x 1220 mm (48" x 48") louvre tested to figure 5.5.

Free Area Table (Free area in sq. feet and sq. metres)

For additional sizes, please visit:

<https://www.c-sgroup.com/architectural-louvers/louvers-airflow-tool>

Width in Inches and Metres									
		18	24	30	36	42	48	54	60
		0.46	0.61	0.76	0.91	1.07	1.22	1.37	1.52
18	0.93	1.33	1.72	2.12	2.52	2.92	3.31	3.71	
	0.46	0.09	0.12	0.16	0.20	0.23	0.27	0.31	0.34
24	1.34	1.92	2.50	3.07	3.65	4.22	4.80	5.38	
	0.61	0.12	0.18	0.23	0.29	0.34	0.39	0.45	0.50
30	1.76	2.51	3.27	4.02	4.78	5.53	6.29	7.04	
	0.76	0.16	0.23	0.30	0.37	0.44	0.51	0.58	0.65
36	2.18	3.11	4.04	4.97	5.91	6.84	7.77	8.71	
	0.91	0.20	0.29	0.38	0.46	0.55	0.64	0.72	0.81
42	2.59	3.70	4.81	5.93	7.04	8.15	9.26	10.37	
	1.07	0.24	0.34	0.45	0.55	0.65	0.76	0.86	0.96
48	3.01	4.30	5.59	6.88	8.17	9.46	10.75	12.04	
	1.22	0.28	0.40	0.52	0.64	0.76	0.88	1.00	1.12
54	3.42	4.89	6.36	7.83	9.30	10.76	12.23	13.70	
	1.37	0.32	0.45	0.59	0.73	0.86	1.00	1.14	1.27
60	3.84	5.49	7.13	8.78	10.43	12.07	13.72	15.36	
	1.52	0.36	0.51	0.66	0.82	0.97	1.12	1.27	1.43
66	4.26	6.08	7.91	9.73	11.56	13.38	15.21	17.03	
	1.68	0.40	0.57	0.73	0.90	1.07	1.24	1.41	1.58
72	4.67	6.68	8.68	10.68	12.69	14.69	16.69	18.69	
	1.83	0.43	0.62	0.81	0.99	1.18	1.36	1.55	1.74
78	5.09	7.27	9.45	11.63	13.82	16.00	18.18	20.36	
	1.98	0.47	0.68	0.88	1.08	1.28	1.49	1.69	1.89
84	5.51	7.87	10.23	12.59	14.94	17.30	19.66	22.02	
	2.13	0.51	0.73	0.95	1.17	1.39	1.61	1.83	2.05
90	5.71	8.16	10.61	13.06	15.51	17.96	20.41	22.86	
	2.29	0.53	0.76	0.99	1.21	1.44	1.67	1.90	2.12
96	6.13	8.76	11.38	14.01	16.64	19.27	21.89	24.52	
	2.44	0.57	0.81	1.06	1.30	1.55	1.79	2.03	2.28
102	6.55	9.35	12.16	14.96	17.77	20.57	23.38	26.19	
	2.59	0.61	0.87	1.13	1.39	1.65	1.91	2.17	2.43
108	6.96	9.95	12.93	15.91	18.90	21.88	24.87	27.85	
	2.74	0.65	0.92	1.20	1.48	1.76	2.03	2.31	2.59
114	7.38	10.54	13.70	16.87	20.03	23.19	26.35	29.52	
	2.90	0.69	0.98	1.27	1.57	1.86	2.15	2.45	2.74
120	7.79	11.14	14.48	17.82	21.16	24.50	27.84	31.18	
	3.05	0.72	1.03	1.34	1.66	1.97	2.28	2.59	2.90
126	8.21	11.73	15.25	18.77	22.29	25.81	29.33	32.85	
	3.20	0.76	1.09	1.42	1.74	2.07	2.40	2.72	3.05
132	8.63	12.32	16.02	19.72	23.42	27.12	30.81	34.51	
	3.35	0.80	1.15	1.49	1.83	2.18	2.52	2.86	3.21
138	9.04	12.92	16.80	20.67	24.55	28.42	32.30	36.17	
	3.51	0.84	1.20	1.56	1.92	2.28	2.64	3.00	3.36
144	9.46	13.51	17.57	21.62	25.68	29.73	33.79	37.84	
	3.66	0.88	1.26	1.63	2.01	2.39	2.76	3.14	3.52
150	9.88	14.11	18.34	22.57	26.81	31.04	35.27	39.50	
	3.81	0.92	1.31	1.70	2.10	2.49	2.88	3.28	3.67
156	10.29	14.70	19.11	23.53	27.94	32.35	36.76	41.17	
	3.96	0.96	1.37	1.78	2.19	2.60	3.01	3.41	3.82
162	10.71	15.30	19.89	24.48	29.07	33.66	38.24	42.83	
	4.11	0.99	1.42	1.85	2.27	2.70	3.13	3.55	3.98
168	11.12	15.89	20.66	25.43	30.20	34.96	39.73	44.50	
	4.27	1.03	1.48	1.92	2.36	2.81	3.25	3.69	4.13
174	11.33	16.19	21.05	25.90	30.76	35.62	40.47	45.33	
	4.42	1.05	1.50	1.96	2.41	2.86	3.31	3.76	4.21
180	11.75	16.78	21.82	26.85	31.89	36.93	41.96	47.00	
	4.57	1.09	1.56	2.03	2.49	2.96	3.43	3.90	4.37
186	12.16	17.38	22.59	27.81	33.02	38.23	43.45	48.66	
	4.72	1.13	1.61	2.10	2.58	3.07	3.55	4.04	4.52
192	12.58	17.97	23.37	28.76	34.15	39.54	44.93	50.33	
	4.88	1.17	1.67	2.17	2.67	3.17	3.67	4.17	4.68
198	13.00	18.57	24.14	29.71	35.28	40.85	46.42	51.99	
	5.03	1.21	1.72	2.24	2.76	3.28	3.80	4.31	4.83

Upper Numerals Imperial Units / Lower Numerals Metric Units