

MODEL VS747

STANDARD CONSTRUCTION

- **Material:** Extruded Aluminum 6063-T6
- **Frame:** 7" (178 mm) Deep, 0.081" (2.1 mm) Wall Thickness
- **Blade:** 7" (178 mm) Deep, 0.070" (1.8 mm) Wall Thickness
- **Blade Spacing:** 3" (76.2 mm) On Center
- **Sill Flashing:** 0.063" (1.6 mm) Formed Aluminum W/ End Dams

OPTIONAL ACCESSORIES


- Bird Screen
- Insect Screen
- Extended Sill Flashing
- Insulated & Non-Insulated Blank Off Panels
- Flanged & Glazing Frames
- Visible Mullions
- Invisible Mullions for Continuous Blade Appearance
- Hinged Access Panels

FINISHES

- **2-Coat Fluoropolymer:** Fluropon Pure® 70% PVDF (AAMA 2605)*
 - **3-Coat Fluoropolymer:** Fluropon Pure® 70% PVDF (AAMA 2605)*
 - **Anodic Finishes:** Class I & Class II, Clear & Bronze Spectrum
 - **Prime Coat:** Recommended When Field Painting
- *Custom Colors Available

SUGGESTED SPECIFICATIONS

- **General:** Furnish and install where indicated on drawings 7" (178 mm) Storm Performance Louver Model VS747 as manufactured by Industrial Louvers, Inc. Delano, MN.
- **Material:** Extruded aluminum frames and blades shall be one piece 6063-T6 alloy, designed to collect and drain water to the exterior at the sill by means of integral gutters in the blades and jamb frames. Frame shall have a minimum material thickness of 0.081" (2.1 mm). Fixed blades shall have a material thickness of 0.070" (1.8 mm). Frames and blades shall be joined by stainless steel fasteners, and frame will be caulked to prevent water penetration to interior wall construction.



REV: NOVEMBER 2025



MODEL VS747

PERFORMANCE


- Free Area = 8.69 ft² (54.3%)
 - Beginning Point of Water Penetration = 1058 fpm / 9194 cfm
 - Intake Airflow @ ΔP of 0.15" Water = 679 fpm / 5900 cfm
 - Exhaust Airflow @ ΔP of 0.15" Water = 755 fpm / 6560 cfm
- *All Ratings Based on 48" x 48" Test Specimen
 *Ratings Include the Effect of a Sill Pan

FREE AREA (ft²)

Louver Height	120 in	5.16	11.34	17.53	23.72	29.90	36.09
	108 in	4.61	10.15	15.68	21.21	26.75	32.28
	96 in	4.07	8.95	13.83	18.71	23.59	28.47
	84 in	3.52	7.75	11.98	16.20	20.43	24.66
	72 in	2.98	6.55	10.13	13.70	17.27	20.85
	60 in	2.43	5.35	8.27	11.20	14.12	17.04
	48 in	1.89	4.16	6.42	8.69	10.96	13.23
	36 in	1.34	2.96	4.64	4.57	6.19	7.80
	24 in	0.80	1.76	2.72	3.68	4.64	5.60
12 in	0.26	0.56	0.87	1.18	1.48	1.79	
Louver Width	12 in	24 in	36 in	48 in	60 in	72 in	

- Effects of blade stiffeners or additional bracing has not been considered.
- Effects of screen or other accessories has not been considered.
- Contact Industrial Louvers for free area of other sizes.
- 1 in = 25.4 mm
- 10.76 ft² = 1 m²

AIR PERFORMANCE



WIND DRIVEN RAIN

	Ventilation Air Velocity	0.0 m/s	0.5 m/s	1.0 m/s	1.5 m/s	2.0 m/s	2.5 m/s	3.0 m/s	3.5 m/s
Rainfall Rate: 3 in/hr	Core Velocity	-	-	-	-	-	-	594 fpm	688 fpm
Wind Velocity: 29 mph	Effectiveness	-	-	-	-	-	-	99.9%	99.8%
	Penetration Class	A	A	A	A	A	A	A	A
Rainfall Rate: 8 in/hr	Core Velocity	-	-	-	300 fpm	393 fpm	486 fpm	588 fpm	686 fpm
Wind Velocity: 50 mph	Effectiveness	-	-	-	99.4%	99.3%	99.1%	98.7%	98.0%
	Penetration Class	A	A	A	A	A	A	B	B



Industrial Louvers, Inc. certifies that the Model VS747 shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to air performance ratings, water penetration ratings, and wind driven rain ratings.

© 2025 Industrial Louvers. All rights reserved.

REV: NOVEMBER 2025



www.IndustrialLouvers.com
 ilinfo@IndustrialLouvers.com

511 South 7th Street, Delano MN 55328
 Tel: 763.972.2981 | Fax: 763.972.2911