BERNER AIR CURTAINS

COMMERCIAL HIGH PERFORMANCE 8
Unheated Indoor/Outdoor Air Curtain - Rocker Switch
Data Sheet

Vestibule Exception Compliance: up to 10 ft. AFF / Optimal Environmental Separation: up to 8 ft. AFF



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (unheated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

5 Year Limited Warranty

Made in USA

outdoor use

MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Net Wt. (lbs)
CH08-F-1025A	25.00	2,297	1,372	536	74%	0.15	1 @ 1/5	28
CH08-F-1030A	30.00	2,584	1,760	825	78%	0.23	1 @ 1/5	33
CH08-F-1036A	36.00	2,308	1,758	989	85%	0.21	1 @ 1/5	38
CH08-F-1042A	42.00	2,425	1,778	1,167	83%	0.24	1 @ 1/5	41
CH08-F-1048A	48.00	2,417	1,827	1,370	80%	0.26	1 @ 1/5	44
CH08-F-1060A	59.00	2,276	1,827	1,684	81%	0.33	1 @ 1/5	52
CH08-F-1072A	72.00	2,185	1,648	1,854	84%	0.35	1 @ 1/5	59
CH08-F-2078A	78.00	2,425	1,769	2,156	83%	0.44	2 @ 1/5	75
CH08-F-2084A	84.00	2,425	1,778	2,334	83%	0.47	2 @ 1/5	83
CH08-F-2096A	96.00	2,417	1,827	2,740	80%	0.53	2 @ 1/5	90
CH08-F-2108A	108.00	2,417	1,810	3,054	80%	0.60	2 @ 1/5	97
CH08-F-2120A	118.00	2,276	1,827	3,368	81%	0.67	2 @ 1/5	104

NOTES:
1. Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance.
2. UL Outdoor use requires remote switch.

MODEL NUMBER CONFIGURATION

CH08-F-1 025 A A-AC-RS-SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor Type	Controls Type	Cabinet Finish
CH08	F	1, 2	025" - 120"	A=Ambient	A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 230/1/50 Z = 480/3/60** Q=600/3/60**	AC (Std.)	RS=Rocker Switch (Std.)	White *(leave blank)* BK=Black **Opt. Cabinet Finish** SS=Stainless Steel CC=Custom Color

**Suitable for 50 Hz*
***Not UL outdoor*

STANDARD CONSTRUCTION
- Low Profile, 8 ½" high x 14 ½" deep
- 1/5 hp AC motor(s) - two speeds
- Factory installed fan speed switch
- White or black powder coated exterior
- Wall & Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle

OPTIONS
- Custom Color or Stainless Steel
- Filter (washable)

VELOCITY PROJECTION: Model CH08-F-1036A			
Distance from Nozzle (in)	40	80	120
Core Velocity (fpm)	874	766	576
Uniformity (%)	90%	88%	87%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Sound level measured 10' (3m) from the unit in free field:
1 motor: Min./Max. Speed: 49/55 dBA
2 motors: Min./Max. Speed: 52/58 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.

Berner.com Berner Air Curtains 800.245.4455
111 Progress Ave. / New Castle / PA / 16101 / USA

DS-130F-RS
October, 2026

©Copyright, 2026 Berner Air Curtains