BERNER AIR CURTAINS

COMMERCIAL HIGH PERFORMANCE 10

Steam Heated Air Curtain - Intelliswitch™

Data Sheet

Vestibule Exception Compliance: up to 14 ft. AFF / Optimal Environmental Separation: up to 10 ft. AFF



Berner International certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program. Rated data shown is for base (steam heated) units. The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

2 Year Limited Warranty

Made in USA

indoor use

MODEL	Nozzle Width (in)	Max Vel. at Nozzle (fpm)	Avg. Outlet Vel. (fpm)	Air Volume (cfm)	Outlet Vel. Uniformity	Power Rating (kW)	Motor(s) @ hp	Coil Output (MBH)	Inlet Pressure (PSIG)	Condensate (lbs/hr)	Air Temp. Rise (°F)	Net Wt. (lbs)
CH10-F-1036S	36.00	3,522	1,916	1,317	80%	0.49	1 @ 1/2	58.6	5	60.4	41°	75
CH10-F-1042S	42.00	3,429	1,709	1,371	82%	0.50	1 @ 1/2	65.1	5	67.1	44°	80
CH10-F-1048S	48.00	4,040	1,833	1,680	90%	0.63	1 @ 1/2	77.8	5	80.1	43°	85
CH10-F-1060S	59.00	4,146	1,541	1,736	85%	0.63	1 @ 1/2	88.7	5	91.4	47°	97
CH10-F-2072S	72.00	3,522	1,916	2,634	80%	0.98	2 @ 1/2	121.6	5	125.3	43°	141
CH10-F-2078S	78.00	3,522	1,805	2,688	80%	0.99	2 @ 1/2	127.9	5	131.9	44°	148
CH10-F-2084S	84.00	3,429	1,709	2,742	82%	1.00	2 @ 1/2	134.1	5	138.2	45°	156
CH10-F-2096S	96.00	4,040	1,833	3,360	90%	1.26	2 @ 1/2	159.7	5	164.6	44°	164
CH10-F-2108S	108.00	4,146	1,656	3,416	85%	1.26	2 @ 1/2	170.6	5	175.8	46°	171
CH10-F-2120S	118.00	4,146	1,541	3,472	85%	1.26	2 @ 1/2	178.7	5	184.2	48°	178
CH10-F-3132S	132.00	4,040	1,855	4,677	80%	1.75	3 @ 1/2	222.6	5	229.4	44°	229
CH10-F-3144S	144.00	4,040	1,833	5,040	90%	1.89	3 @ 1/2	241.6	5	249.0	44°	239

See sheets EP-146F-AC-DS & EP-146F-EC-DS for amp draws/total load requirements.
480/3/60 - 600/3/60 power supply includes transformer housing, See drawing CH10F-S-480INT

NOTES:
1. Standard connection same end supply/return.
2. Coil should be field supplied with a solenoid/control valve that energizes only when air curtain is energized. Consideration must be taken for freeze protection when necessary.
3. Coil performance based on 65°F entering air temperature.
4. Maximum leaving air temperature shall not exceed 120F.
5. Consult factory for alternate steam pressures.
6. Operation of standard motor (AC) at 50Hz will generate a 17% reduction in performance; no reduction for optional EC motors.

MODEL NUMBER CONFIGURATION

CH10-F-1 036 S A-AC-DL-R-SS

Series	Version	# of Motors	Opening Width	Heat	Voltage	Motor	Controls Type	Opt. Display	Cabinet Finish
CH10	F	1, 2, 3	036" - 144"	S=Steam Heated	***AC & EC motors*** A = 120/1/60* B = 208/1/60 J = 240/1/60 V = 230/1/50 A-XH = 480/3/60 † A-XI = 600/3/60 †	AC (Std.) EC (Opt.)	DL=Intelliswitch - Pushbutton (Std.) CB=Berner AIR BASIC (Opt.) CM=Berner AIR BMS (Opt.)	R=Remote Display	White *(leave blank)* BK=Black **Opt. Cabinet Finish** SS=Stainless Steel CC=Custom Color

**Suitable for 50 Hz*
† Cabinet width increases for transformer, see EP-146 for lengths

STANDARD CONSTRUCTION

- 13 ¾" high x 15 ½" deep
- 1/2 hp AC motor(s) - ten speeds
- Pushbutton interface with Intelliswitch™ digital controller
- White or black powder coated exterior
- Wall & Top Mounting
- High efficiency, low noise, articulating, three vane, Pro-V Nozzle
- Factory installed coil

OPTIONS

- 1/2 hp EC motor(s) - ten speeds
- Berner AIR® BASIC (smart control)
- Berner AIR® BMS (smart control with BACnet and Modbus)
- Custom Color or Stainless
- Filter (washable)

VELOCITY PROJECTION: Model CH10-F-1036S				
Distance from Nozzle (in)	40	80	120	160
Core Velocity (fpm)	1259	876	856	742
Uniformity (%)	83%	88%	92%	96%

ASHRAE 90.1-2019 vestibule exception requires, "a jet velocity of not less than 6.6 feet per second (400 fpm; 2.0 m/s) at 6.0 in (15 cm) above the floor."

Sound level measured 10' (3m) from the unit in free field:
1 motor: Min./Max. Speed: 53/56 dBA
2 motors: Min./Max. Speed: 56/59 dBA
3 motors: Min./Max. Speed: 59/61 dBA

Sound data is not AMCA certified.

Berner reserves the right to alter specifications without prior notice.

Berner.com Berner Air Curtains 800.245.4455
111 Progress Ave. / New Castle / PA / 16101 / USA

DS-146F-DS
October, 2026

©Copyright, 2026 Berner Air Curtains