


Plug Fans

- backward curved impellers



Dongguan Wolter Chemco Ventilation Ltd. certifies that the Series PFE shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

Air in Motion.

Wolter Fans.

R15

wolter 

Symbols and technical formula symbols



Symbol	Meaning	Symbol	Meaning	Symbol	Meaning
	5-step transformer control		Speed control switch		Wiring diagram
	Continuously adjustable transformer control		Off-Switch		flame proof
	Continuously adjustable electronic control		Weight		Dimensions
	Motor protection switch		Protection class		Accessories

Symbol	Designation	Unit
A	Cross-section	m ²
C ₂	Flow speed	m/s
C _{400V}	Capacitor	μF
D ₂	Impeller diameter	m
d	Pipe diameter	m
d _g	Equivalent diameter	m
g	Gravitational speed acceleration	m/s ²
I _N	Rated current	A
I _A / I _N	Ratio of starting current to rated current	
ΔI	Current increase in component voltage area	%
l	Pipe or channel length	m
L _{PA}	Sound pressure level A-weighted	dB(A)
L _{WA}	Sound power level A-weighted	dB(A)
L _{WA}	Sound power level to surrounding	dB(A)
L _{WA}	Inlet sound power level induct	dB(A)
L _{WA}	Outlet sound power level induct	dB(A)
L _{WA5}	Inlet sound power level unducted	dB(A)
L _{WA6}	Outlet sound power level unducted	dB(A)
n	Speed	1/min (bzw. 1/s)
P ₁	motor power consumption	kW (bzw. W)
p _s (p _{st})	Static pressure	Pa
Δ p _{st}	Differential static pressure	Pa
Δp _{fa min}	min. required conter pressure	Pa
p _d	Dynamic pressure	Pa
p _{d2}	Dynamic pressure at fan outlet	Pa
Δ p _d	Differential dynamic pressure	Pa
p _t	Total pressure	Pa
Δ p _t	Difference of total pressures	Pa
T	Temperature in Kelvin	K
t	Temperature in Celsius	°C
t _R	max. permissable medium temperature	°C
u ₂	Circumferential speed of the impeller (outside)	m/s
\dot{V}	Volume flow	m ³ /h (bzw. m ³ /s)
ρ	Density of medium	kg/m ³
η	Efficiency	-
φ	Volume number	-
ψ	Pressure number	-
ζ	Coefficient of drag	-
λR	Coefficient of friction of channel or pipe	-

Table of Content

Symbols and technical formula symbols	Page II
Contents	Page 1
Technical Description	Page 2
Impeller	Page 2
Inlet Cone	Page 2
Overlap	Page 2
Assembly	Page 2
Sound Levels	Page 2
Performance Curves	Page 2
Delivery Options	Page 2
Accessories	Page 2
Dimensions	Page 3 - 4
Fan Efficiency Grade	Page 5
Performance curves	Page 6 - 20

Subject to change without prior notice.

Technical Description



Impeller

The centrifugal plug fan impellers are made of steel / aluminum / thermoplastic material with backward curve blades. The impeller is aerodynamically designed for high efficiency and low power consumption. The maximum tip speed of the impeller is 70m/s. The impellers are optimized for stable performance and low noise and balanced according to G2.5 to DIN ISO 1940/1 or AMCA 204.

The impeller come with either GG-hub or precision-cast-aluminum alloy hub with steel insert for use with taper lock bushes. GG-hub or Precision-cast- aluminum alloy with straight bore hole are also available upon request. The blades are made of powder coated steel / GI sheet steel / aluminum / thermoplastic.

Inlet Cone

The inlet cone is made of powder coated / GI sheet steel / thermoplastic. The inlet cone allows a uniform and stable airflow into the impeller assuring cataloged performance.

Overlap

The overlap distance is determined by empirical and airflow tests which take into account the aerodynamic characteristics of the impeller.

Assembly

The complete assembly consists of the motor, impeller and inlet cone. The mounting base is manufactured from galvanized steel sheet.

Sound levels

In order to make possible an assessment of sound projection adequate to the human ear the A-assessed description of sound levels has been chosen. The ascertaining of the sound power level follows the reverberant room method according to AMCA 300. The sound power levels shown on each performance curve, LwoA, refer to the overall sound power "A-Weighted" levels. The computed sound power levels were converted into A-Weighted levels using adjustments to the octave band spectrum as follows:

Centre Frequency Hz	63	125	250	500	1000	2000	4000	8000
A-Weighted Adjustment	-26.2	-16.1	-8.6	-3.2	0	1.2	1.0	-1.1

The overall sound pressure levels, LpoA, can be calculated from the overall sound power levels as follows:

- 1) Free Field Conditions: $L_{poA} = L_{woA} - (20 \log_{10} d) - 11$
- 2) Room Conditions: $L_{poA} = L_{woA} - (20 \log_{10} d) - 7$

Where: d = distance from fan in meters

Performance curves

The performance curves have been established using the inlet test method in the test chamber according to AMCA 210 installation Type A (free inlet, free outlet).

The curves indicate as a function of the volume flow:

- ▶ the static pressure increase p_s for constant speed (heave black lines)
- ▶ constant lines of shaft power P_w (red Lines)
- ▶ constant lines of sound power level LwoA (blue lines)

All values relate to an air density: $\rho = 1,2 \text{ kg/m}^3$ at 20°C

The dynamic pressure p_{d2} and the flow speed c_2 respectively stated in the diagrams refer to the outlet of impeller.

Delivery Options


There are 3 different options:

- a) Impeller with inlet cone
- b) Impeller with inlet cone + Mounting assembly
- c) Impeller with inlet cone + Mounting assembly + Motor

Accessories

The following accessories are available:


- 1) Elastic Flexible connectors
- 2) Damper
- 3) Adjustable sliding (mechanical type) for air volume regulation and control
- 4) Acoustic or single skin enclosure



Size	b [mm]	H [mm]	ØD_A [mm]	ØD_3 [mm]	ØL_k [mm]	t [mm]	z x Ød [mm]	H_{LD} [mm]	n_{max} [1/min]
280	82	117	300	323	280	4	6 x 7	169	4650
315	92	126	355	360	325	5	6 x 7	178	3990
355	100	144	383	406	344	6	6 x 7	196	3650
400	112	160	423	456	386	7	6 x 7	220	3255
450	126	179	466	512	432	7	6 x 7	243	2925
500	139	200	515	570	485	8	8 x 9	277	2580
560	160	229	570	640	544	8	8 x 9	314	2330
630	180	253	635	720	605	9	8 x 9	353	2080
710	202	283	700	810	670	10	8 x 9	394	1810
800	227	320	778	912	750	12	12 x 12	447	1630
900	255	357	875	1023	844	14	12 x 12	503	1460
1000	282	400	980	1120	945	16	12 x 12	561	1310
1120	316	448	1044	1254	1080	16	12 x 12	639	1200
1250	352	502	1220	1400	1180	18	14 x 14	696	1100
1400	395	564	1360	1568	1310	18	14 x 14	796	1000

Note: We reserve the right to alter measurements without notice in case of technical improvements.

Dimensions



Size	A	B	B1	B2	C	D	H1	H2	L _{max.}	L1	L3	Mtr
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	Frm Size
280	35	396	310	346	396	14	50	248	640	360	465	71-100
315	35	440	360	396	440	14	50	270	650	360	465	71-112
355	35	480	400	436	480	14	50	290	650	300	425	71-80
400	35	520	450	486	520	14	50	310	790	380	505	90-112
450	35	590	510	546	590	14	50	345	815	400	525	80-112
500	40	650	550	590	650	14	63	388	990	500	625	132
560	40	720	610	650	720	14	63	423	1030	440	605	90-112
630	45	800	685	725	800	14	63	463	1070	620	785	132-160
710	50	880	770	810	880	18	80	520	1175	460	625	90-112
800	50	1000	850	890	1000	18	80	580	1230	660	825	132-160
900	50	1120	960	1000	1120	18	80	610	1290	510	675	112
1000	50	1250	1080	1120	1250	18	80	705	1415	700	865	132-160
1120	60	1400	1210	1250	1400	18	100	800	1710	600	805	112-132
1250	60	1560	1360	1400	1560	18	100	880	1860	740	945	160-180
1400	60	1750	1500	1540	1750	18	100	945	2010	650	860	132
										800	1010	160-180
										700	910	132
										900	1110	160-180
										1000	1210	160-200
										1200	1410	200-225
										1400	1610	250-280
										1300	1510	225-250
										1500	1710	280-315
										1400	1610	250
										1600	1810	280-315

Note: We reserve the right to alter measurements without notice in case of technical improvements.

AMCA - FEG Rating


Fan Efficiency Grade: PFE Series



Certified FEGs are determined in accordance with AMCA 205-12 Energy Efficiency Classification for fans. In conjunction with AMCA 211-13 (Rev. 2015) Certified Ratings Program, Product Rating Manual for Fan Air Performance. This classification is based on fan peak (optimum) total efficiency for a given fan speed, fan size and application category. For the purpose of energy classification, the peak efficiency can be determined at a speed not higher than the maximum design speed of the fan.


The AMCA Certified Ratings Seal applies to the Fan Efficiency Grade (FEG) for PFE series Inline Centrifugal Plug Fan model PFE 280 to PFE 1400 as shown in the table below.

Fan Model No.	Max. Fan Speed (rpm)	Fan Outlet Area (m2)	Fan Efficiency Grade (FEG)	Fan Model No.	Max. Fan Speed (rpm)	Fan Outlet Area (m2)	Fan Efficiency Grade (FEG)
PFE 280	4650	0.0750	90	PFE 710	1810	0.4582	80
PFE 315	3990	0.0945	90	PFE 800	1630	0.5776	80
PFE 355	3650	0.1147	90	PFE 900	1460	0.7290	80
PFE 400	3255	0.1443	85	PFE 1000	1310	0.8904	80
PFE 450	2925	0.1825	85	PFE 1120	1200	1.1198	80
PFE 500	2580	0.2227	85	PFE 1250	1100	1.3911	80
PFE 560	2330	0.2875	80	PFE 1400	1000	1.7472	80
PFE 630	2080	0.3630	80				



Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	⚖ [kg]	Typ	Art.Nr.	⚖ [kg]	Wheel diameter	D =	291	mm
PFE 280		26				Number of blades	z =	6	
						Outlet Area	A =	0.0750	m²
						Moment of inertia	J =	0.056	kg·m²
						Speed limit	n_{max} =	4650	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	Wt. [kg]	Typ	Art.Nr.	Wt. [kg]	Wheel diameter	D =	327	mm
PFE 315		37				Number of blades	z =	6	
						Outlet Area	A =	0.0945	m²
						Moment of inertia	J =	0.076	kg·m²
						Speed limit	n _{max} =	3990	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	⚖ [kg]	Typ	Art.Nr.	⚖ [kg]	Wheel diameter	D =	365	mm
PFE 355		40				Number of blades	z =	6	
						Outlet Area	A =	0.1147	m²
						Moment of inertia	J =	0.136	kg·m²
						Speed limit	n_{max} =	3650	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	♁ [kg]	Typ	Art.Nr.	♁ [kg]	Wheel diameter	D =	410	mm
PFE 400		50				Number of blades	z =	6	
						Outlet Area	A =	0.1443	m²
						Moment of inertia	J =	0.208	kg·m²
						Speed limit	n _{max} =	3255	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	⚖ [kg]	Typ	Art.Nr.	⚖ [kg]	Wheel diameter	D =	461	mm
PFE 450		60				Number of blades <th>z =</th> <th>6</th> <td></td>	z =	6	
						Outlet Area <th>A =</th> <th>0.1825</th> <th>m²</th>	A =	0.1825	m²
						Moment of inertia <th>J =</th> <th>0.393</th> <th>kg·m²</th>	J =	0.393	kg·m²
						Speed limit <th>n_{max} =</th> <th>2925</th> <th>1/min</th>	n _{max} =	2925	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	♁ [kg]	Typ	Art.Nr.	♁ [kg]	Wheel diameter	D =	510	mm
PFE 500		75				Number of blades	z =	6	
						Outlet Area	A =	0.2227	m²
						Moment of inertia	J =	0.567	kg·m²
						Speed limit	n _{max} =	2580	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	♁ [kg]	Typ	Art.Nr.	♁ [kg]	Wheel diameter	D =	572	mm
PFE 560		85				Number of blades	z =	6	
						Outlet Area	A =	0.2875	m²
						Moment of inertia	J =	0.992	kg·m²
						Speed limit	n _{max} =	2330	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	♁ [kg]	Typ	Art.Nr.	♁ [kg]	Wheel diameter	D =	642	mm
PFE 630		105				Number of blades	z =	6	
						Outlet Area	A =	0.3630	m²
						Moment of inertia	J =	1.602	kg·m²
						Speed limit	n _{max} =	2080	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	⚖ [kg]	Typ	Art.Nr.	⚖ [kg]	Wheel diameter	D =	722	mm
PFE 710		130				Number of blades	z =	6	
						Outlet Area	A =	0.4582	m²
						Moment of inertia	J =	2.723	kg·m²
						Speed limit	n _{max} =	1810	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet Lw_{oA} sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	■ [kg]	Typ	Art.Nr.	■ [kg]				
PFE 800		200					Wheel diameter	D =	810 mm
							Number of blades	z =	6
							Outlet Area	A =	0.5776 m²
							Moment of inertia	J =	5.034 kg·m²
							Speed limit	n_{max} =	1630 1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	⚖ [kg]	Typ	Art.Nr.	⚖ [kg]	Wheel diameter	D =	910	mm
PFE 900		280				Number of blades <th>z =</th> <th>6</th> <td></td>	z =	6	
						Outlet Area <th>A =</th> <th>0.7290</th> <th>m²</th>	A =	0.7290	m²
						Moment of inertia <th>J =</th> <th>9.214</th> <th>kg·m²</th>	J =	9.214	kg·m²
						Speed limit <th>n_{max} =</th> <th>1460</th> <th>1/min</th>	n _{max} =	1460	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	Wt [kg]	Typ	Art.Nr.	Wt [kg]	Wheel diameter	D =	1005	mm
PFE 1000		330				Number of blades	z =	6	
						Outlet Area	A =	0.8904	m²
						Moment of inertia	J =	14.37	kg·m²
						Speed limit	n _{max} =	1310	1/min

Explanation of symbols see page II


Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.



Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet Lw_{oA} sound power levels for installation Type A: free inlet, free outlet.




Typ	Art.Nr.	■ [kg]	Typ	Art.Nr.	■ [kg]		Wheel diameter	D =	1258	mm
PFE 1250		585					Number of blades	z =	6	
							Outlet Area	A =	1.3911	m²
							Moment of inertia	J =	37.11	kg·m²
							Speed limit	n_{max} =	1100	1/min

Explanation of symbols see page II

Fan test laboratory AMCA 210 Test Chamber. Performance certified is for installation type A-Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories).

The A-weighted sound ratings shown have been calculated per AMCA International Standard 301. Values shown are for outlet LwoA sound power levels for installation Type A: free inlet, free outlet.



Typ	Art.Nr.	♁ [kg]	Typ	Art.Nr.	♁ [kg]	Wheel diameter	D =	1408	mm
PFE 1400		700				Number of blades	z =	6	
						Outlet Area	A =	1.7472	m²
						Moment of inertia	J =	56.32	kg·m²
						Speed limit	n _{max} =	1000	1/min

Explanation of symbols see page II

Wolter Sales Network

Inland

Ing. Günther Rößler
D-07619 Schkölen
Tel. (+49) 03 66 94 / 22 359
Fax (+49) 03 66 94 / 22 357
guenther.roessler@wolterfans.de

Mattias Industrievertretungen
D-16259 Bad Freienwalde
Tel. (+49)03344/301994
Fax (+49)03344/301996
thomas.mattias@wolterfans.de

Industrieservice Drexler
D-49080 Osnabrück
Tel. (+49) 0 541 / 20 04 88 3
Fax (+49) 0 541 / 20 04 88 4
wolfgang.drexler@wolterfans.de

Burkhardt Projekt GmbH
D-67583 Guntersblum
Tel. (+49) 0 62 49 / 82 01
Fax (+49) 0 62 49 / 28 58
info@bp-wolter.de

Friedrich Glock
D-97980 Bad Mergentheim
Tel. (+49) 0 79 31 / 37 44
Fax (+49) 0 79 31 / 28 58
friedrich.glock@wolterfans.de

Europe

Danmark:

Air-Con Danmark A/S
DK-8400 Ebeltoft
Tel. (+45)086/345111
Fax (+45)086/345810
jbj@air-con.dk

Hungary:

Air-Technik Légtechnikai Kft.
HU-2040 Budaörs
Tel. (+36)023/428533
Fax (+36)023/428544
bp.air-technik@troges.hu

Ireland:

Finheat Ltd.
IE-Dublin 12, Walkinstown
Tel. (+353)01/4564066
Fax (+353)01/4564071
sales@finheat.com

Lithuania:

JSC Saldos Prekyba
LT-78109 Siauliai
Tel. (+37)041/540212
Fax (+37)041/596176
prekyba@salda.lt

Netherlands:

AirFan B. V.
NL-7442 CX Nijverdal
Tel. (+31)054/8366366
Fax (+31)054/8365320
ventilatie@airfan.nl

Rucon B. V. Ventilatoren

NL-3840 AG Harderwijk
Tel. (+31)034/1411670
Fax (+31)034/1411690
verkoop@rucon.nl

Österreich:

Wolter Werksvertretung Österreich
A-4040 Linz
Tel. (+43) 07 32 / 75 77 07
Fax (+43)07 32 / 75 77 07 75
wolter.linz@aon.at

Wolter GmbH Maschinen-und Apparatebau KG

Am Wasen 11
D-76316 Malsch / Germany
Tel. +49 (0) 7204/9201-0
Fax +49 (0) 7204/9201-11
www.wolter.eu
info@wolter.eu

Poland:

Wentoprodukt
44-100 Gliwice
Tel. (+48)32 331-34-24
Fax (+48)32 729-76-53
biuro@wentoprodukt.pl

Portugal:

Safe Park Ventilação Industrial Lda.
P-2675-240 Odivelas
Tel. (+351) 21 93 / 75 265
Fax (+351) 21 93 / 86 061
safepark@netcabo.pt

Russia:

Euroclimat-Prof
RU-107082 Moskau
Tel. (+7) 4 95 / 97 57 530
Fax (+7) 4 95 / 97 57 530
gso@euroclimat.ru

Schweiz:

Anson AG Zürich
CH-8055 Zürich
Tel. (+41) 0 44 / 46 11 111
Fax (+41) 0 44 / 46 13 111
info@anson.ch

Ventra Technik AG

CH-8599 Salmsach
Tel. (+41) 0 71 / 46 11 447
Fax (+41) 0 71 / 46 11 448
ventra@bluewin.ch

Turkey:

Air Trade Centre Ltd Sti Türkiye,
TR-34418 Seyrantepe / Istanbul
Tel. (+90) 02 12 / 28 34 510
Fax (+90) 02 12 / 27 83 964
atc.turkey@airtradecentre.com

United Kingdom:

Wolter UK Ltd.
GB-B37 7UQ Solihull
Tel. (+44) 01 21 / 63 55 390
Fax (+44) 01 21 / 63 55 391
info@wolteruk.com

Middle East and North Africa

Egypt:

Tiba Engineering Industries Co.
Nasr City, Cairo
Tel. (+2) 02 / 40 22 866
Fax (+2) 02 / 40 44 771
tibaengineering@manz-group.com

Israel:

Lea Ventilation Industries Ltd.
IL-27113 Kiriyyat-Bialik, Israel
Tel. (+972) 0 48 / 76 23 57
Fax (+972) 0 48 / 76 20 51
mail@lea.co.il

United Arab Emirates, Kuwait, Lebanon:

Wolter Ventilation LLC
Energy International
P.O. Box 3562 Sharjah, UAE
Tel. (+971) 06 / 53 43 477
Fax (+971) 06 / 53 43 756
energys@emirates.net.ae

Asia

China Mainland:

Taizhou Wolter Ventilation Co. Ltd.
Hengjie, Lujiao District
Taizhou City, Zhejiang
Tel. (+86) 576 / 26 22 666 (26 52 888)
Fax (+86) 576 / 26 56 830

Hongkong:

Wolter Asia Ltd.
Hong Kong
Tel. (+852) 0 24 / 56 01 98
Fax (+852) 0 24 / 56 02 90
info@wolter.com.hk

India:

Wolter Ventilators India Pvt. Ltd.
867 D, Block-A, Sushant Lok, Phase-I,
Gurgaon - 122009 (Haryana)
Tel. +91 124 2577797, 4261001-3
sales@wolterindia.in

Indonesia:

PT. Agung Kipas Kastara.
ID-14440 Jakarta Indonesia
Tel. +62 (0) 21 / 6667 6925, 6667 6926
Fax +62 (0) 21 / 6667 6927
indowolter@cbn.net.id

Korea:

Kaceco-Wolter
14-1, Dang-dong, Gunpo-shi, Gyeonggi-do
Tel. +82 (0) 31 / 4773 104
Fax +82 (0) 31 / 4773 132
wolter@kaceco.com / info@kaceco.com

Malaysia:

Vibrantech (M) Sdn Bhd.
47200 Petaling Jaya Selangor, Malaysia
Tel. +603 (0) 7847 3500
Fax +603 (0) 7847 3380
sales@vibrantech-sb.com

Singapore:

Wolter Pte. Ltd.
SG-569738 Singapore
Tel. (+65) 0 63 / 52 95 48
Fax (+65) 0 63 / 52 95 47
info@wolterfans.com.sg

Sri Lanka:

Sirocco Air Technologies (Pvt) Ltd.
28/12, Gemunu Mawatha, Kotuwegoda,
Rajagiriya, Sri Lanka
Tel. +94 11 7 392 010
Fax +94 11 7 392 015
suren@sairt.com

Taiwan:

Waxlink International Co., Ltd.
8F No. 218 Roosevelt Rd., Sec. 6
Taipei, Taiwan
Tel. (+886) 02 / 89 32 11 96
Fax (+886) 02 / 89 32 11 97
waxlink.tech@msa.hinet.net

Thailand:

Wolter Ventilation Co., Ltd.
Thamai Kratumban Samutsakorn 74110
Thailand
Tel. +66 (0) 3486 6555
Fax +66 (0) 3486 6599
natiphan@wolterfan.com

Australia

The Sydney Fan Company.
NSW 2147, Sydney, Australia
Tel. +61 (0) 2 / 9624 4000
Fax +61 (0) 2 / 9624 4100
sales@thesydneyfancompany.com





Reference: **R15**, V2017/July, Printed in July, 2017